
# **292156-2** • ACTIVE

### AMP CT

TE Internal #: 292156-2 AMP CT, Connector Assembly, Plug to Plug Relay Header, Wire-to-Board / Wire-to-Wire, 6 Position, 2 mm [.078 in] Centerline, 1 Row, White, Signal

### View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings



Connector Product Type: Connector Assembly Connector & Housing Type: Plug to Plug Relay Header Connector System: Wire-to-Board, Wire-to-Wire Number of Positions: 6

# Centerline (Pitch): 2 mm [.078 in ]

# Features



### Product Type Features

Connector Product Type	Connector Assembly
Connector & Housing Type	Plug to Plug Relay Header
Connector System	Wire-to-Board, Wire-to-Wire
Sealable	No
Configuration Features	
Number of Positions	6
Number of Rows	1
Electrical Characteristics	
Operating Voltage	125 V
Contact Features	
Contact Layout	In-line
Contact Retention Within Housing	Without
Contact Type	Dire
Contact Type	Pin

**C** For support call+1 800 522 6752

AMP CT, Connector Assembly, Plug to Plug Relay Header, Wire-to-Board / Wire-to-Wire, 6 Position, 2 mm [.078 in] Centerline, 1 Row, White, Signal



Contact Current Rating (Max)	2 A
Mechanical Attachment	
Strain Relief	Without
Panel Mount Feature	Without
Mating Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon 66
Centerline (Pitch)	2 mm[.078 in]
Housing Color	White
Dimensions	
Connector Length	7.8 mm[.307 in]
Panel Thickness (Recommended)	.81 – 1.6 mm[.032 – .063 in]
Connector Height	12 mm[.472 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

**Operation/Application** 

Circuit Application	Signal
Industry Standards	
CSA Rating	Certified
Approved Standards	UL Recognized
UL Flammability Rating	UL 94V-0
UL File Number	E28476
UL Rating	Recognized
Agency/Standard	CSA, UL
CSA Certified	Yes
CSA File Number	LR 7189
Packaging Features	
Packaging Quantity	800
Packaging Method	Bag & Box

# Product Compliance

**C** For support call+1 800 522 6752

AMP CT, Connector Assembly, Plug to Plug Relay Header, Wire-to-Board / Wire-to-Wire, 6 Position, 2 mm [.078 in] Centerline, 1 Row, White, Signal



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on

requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# **Compatible Parts**



# Also in the Series AMP CT

AMP CT, Connector Assembly, Plug to Plug Relay Header, Wire-to-Board / Wire-to-Wire, 6 Position, 2 mm [.078 in] Centerline, 1 Row, White, Signal





# Customers Also Bought



CT RELAY HDR ASSY FREE HANGING



# Documents

Product Drawings CT RELAY HDR ASSY FREE HANGING

English

**CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_292156-2\_A.2d\_dxf.zip

**C** For support call+1 800 522 6752

AMP CT, Connector Assembly, Plug to Plug Relay Header, Wire-to-Board / Wire-to-Wire, 6 Position, 2 mm [.078 in] Centerline, 1 Row, White, Signal



English

Customer View Model ENG\_CVM\_CVM\_292156-2\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_292156-2\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages 2.0MM\_AMP\_CT\_CONNECTOR\_SERIES\_QUICK\_REF\_GUIDE

English

Product Specifications AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

Japanese

**Product Specification** 

Japanese

Product Environmental Compliance

MD\_292156-2\_010220182332\_dmtec

English

MD\_292156-2\_010220182332\_dmtec

English