W58-XC4C12A-1 ✓ ACTIVE

Potter & Brumfield | Potter & Brumfield W58

TE Internal #: 3-1393249-9

Circuit Breakers, Thermal, Series Trip, White with Black Rate Marking, Red Trip Band Button Color, 250 VAC Voltage Rating AC,

Potter & Brumfield W58

View on TE.com >



Relays, Contactors & Switches > Circuit Breakers



Circuit Breaker Type: Thermal
Circuit Function: Series Trip

Illuminated: No

Button Color: White with Black Rate Marking, Red Trip Band

Voltage Rating AC: 250 VAC

Features

Product Type Features

Illumination Type	No Light
Product Type	Circuit Breaker
Actuator Type	Push to Reset
Circuit Breaker Type	Thermal
Illuminated	No

Configuration Features

	.47 – .48 (Diameter) in
Earthing Switch	Without
Circuit Function	Series Trip

Electrical Characteristics

Voltage Rating AC	250 VAC
Voltage Rating DC	50 VDC
Circuit Breaker Current Rating	1 A
Interrupt Capacity	2000A @ 50VDC or 1000A @ 250VAC

Body Features

Button Color	White with Black Rate Marking, Red Trip
	Band

Contact Features



Pole Configuration	1
Trip Time at 200%	10 – 45 seconds
Termination Features	
Circuit Breaker Termination Type	6-32 Screws 90° (Screws Installed)
Mechanical Attachment	
Mounting Hardware Packaging	Assembled to Bushing
Mounting Options	Knurled Nut/Lockwasher
Mounting Bushing	15/32 x .3" [7.62mm] Long, Black
Circuit Breaker Mounting Type	Panel Mount

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 4-1393247-9 55-001B=NUT,.468-32,HEX,.567,B

Also in the Series | Potter & Brumfield W58



Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1393249-9_K.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1393249-9_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393249-9_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

W58 Push To Reset Only Thermal Circuit Breaker

English

Industrial Relays Quick Reference Guide

English

Industrial Relays Quick Reference Guide

Japanese

Industrial Relays Quick Reference Guide

Flyer - UL1500 Ignition Protected Circuit Breakers

English