3-2106003-2 ACTIVE

LUMAWISE | Insulation Displacement Connectors Closed End

TE Internal #: 3-2106003-2

Insulation Displacement Connectors Closed End, Poke-In Connectors, Wire-to-Board, 2 Position, 4 in [.16 mm] Centerline,

Printed Circuit Board

View on TE.com >



Connectors > Lighting Connectors > Poke-In Connectors



Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): .16 mm [4 in]

Sealable: No

Connector & Contact Terminates To: Printed Circuit Board

Features

Product Type Features

| Connector Type | Connector Assembly |
|---|-----------------------|
| Connector Style | Receptacle |
| Connector System | Wire-to-Board |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features | |
| Number of Positions | 2 |
| Contact Features | |
| Contact Current Rating (Max) | 6 A |
| Termination Features | |
| Termination Method to Printed Circuit Board | Surface Mount |
| Mechanical Attachment | |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Centerline (Pitch) | .16 mm[4 in] |
| Dimensions | |
| Connector Height | .23 mm[5.8 in] |



| Wire Size | 24 – 22 AW | G |
|------------|------------|----|
| VVire Size | 24 – 22 AV | V(|

Usage Conditions

| Operating Temperature Range | -40 - 105 °C[-40 - 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

| Circuit Application | Power | |
|---------------------|-------|--|

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






TE Part # 3-2106431-2 Connector, SMT-IDC PASS THRU, 2 POS, 24

TE Part # 7-2106003-2 Connector, SMT-IDC,2 pos, 24AWG, black

Also in the Series | Insulation Displacement Connectors Closed End



Ballast Connectors(23)



PCB Headers & Receptacles(1)



Poke-In Connectors(66)

Customers Also Bought



MICRO-MATCH SMD FTE



TE Part #794615-6
PANEL MT DBL ROW HSG 6 POS



TE Part #1-794612-0
PIN CONT 20-24 TIN PLATE L/P





TE Part #2106056-2 Assembly, Right Angle SMT Header, 2-Posi



TE Part #3-2106431-2 Connector, SMT-IDC PASS THRU, 2 POS, 24



TE Part #2118706-2 1 PC STD SHIELD, CRS-13.66X12.70X2. 54MM



Documents

Product Drawings

Connector, SMT-IDC, 2 POS, 24 AWG

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_3-2106003-2_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-2106003-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-2106003-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

IDC_SSL_CONNECTOR

English

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English