Wiha SoftFinish® ESD.

For use on electrostatically sensitive components.



For work on electrostatically sensitive devices and assemblies, there is no better screwdriver than the Wiha SoftFinish® ESD, with integrated soft zone in the multi-component- handle. The dissipative handle with a surface resistance of 10⁶ - 10⁹ ohms discharges the electrostatic energy in a controlled manner to protect devices at risk from electrostatic discharge.

The ergonomic handle form was developed from the basis of extensive scientific investigations in cooperation with the Fraunhofer Institute. The result is a multi-component handle with a seamless outer form. Each hand size adapts perfectly to screwdriver, there are no pressure points while working and loading of the finger joints is minimised.



The hard handle core consists of impact resistant polypropylene. The thermoplastic elastomer handle provides for a pleasant, safe and slip-proof grip. The inseparable handle is connected to the core by a moulding process. The high-quality blade of chromevanadium-molybdenum steel is through hardened and mattechrome plated. The Wiha ChromTop® blade tip ensures a perfect fit in every screw head.

Wiha SoftFinish® ESD screwdrivers correspond to the internationally specified ESD standards IEC 61340-5-1.



Wiha SoftFinish® ESD.

- Dissipative handle designed to discharge uniformly, surface resistance 10⁶ - 10⁹ ohms
- Meets ESD standard IEC 61340-5-1
- Ergonomic SoftFinish® multicomponent handle guarantees comfortable work and optimised handling
- Blade made of high-quality CVM steel, through hardened and chrome plated
- Wiha ChromTop® blade tip ensure a perfect fit in every screw head



Wiha SoftFinish® ESD.

For use on electrostatically sensitive components.

For TORX® screws.



362ESD SoftFinish® ESD TORX® screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	(*)	≕ ■	•1	===	-	
31432	T3	60	2.5	164	23	10
27148	T4	60	2.5	164	23	10
27641	T5	60	3.5	164	23	10
27149	T6	60	3.5	164	23	10
31901	T7	60	3.5	164	23	10
22436	T8	60	3.5	164	23	10
27145	T9	60	4.0	171	30	10
27144	T10	80	4.0	191	30	10
27146	T15	80	4.0	191	30	10
27147	T20	100	4.0	218	36	10

Sets.



302ESD HK5 01 SoftFinish® ESD slotted/ Phillips screwdriver set, 5 pcs.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	Series					
27252	302ESD H	K5 01		1		
1	302ESD	3.0x100	4.0x100			
⊕	311ESD	PH0x60	PH1x80	PH2x100		



SoftFinish® ESD TORX® screwdriver set, 5 pcs.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.





Safety Notice:

Wiha ESD screwdrivers are noninsulated, therefore not suitable for working on live

