



Safety Notice:
Wiha ESD screwdrivers are non-insulated, therefore not suitable for working on live parts.

Wiha SYSTEM 4.

Ideal for precision work.

SYSTEM 4 display and ESD set.



Telescopic



269 VB1 SYSTEM 4 display.
Acryl glass display with 85 pieces.

| Order-No. | Series | | | | |
|-----------|---------|--|-------|-------|-----|
| 00620 | 269 VB1 | | | | |
| | 2691 | 4xSYSTEM 4 SoftFinish®-telescopic handle | | | |
| ⓪ | ⓪ 269 | 4x4.0 | | | |
| ⓪ | ⓪ 269 | 7x1.5 | 7x2.0 | | |
| ⊕ | ⊕ 269 | 7xPH000 | 7xPH0 | | |
| ⊗ | ⊗ 269 | 7x1.5 | 7x2 | 7x2.5 | 7x3 |
| ⊛ | ⊛ 269 | 7xT6 | 7xT7 | 7xT10 | |



Telescopic



2691 T11 ESD SYSTEM 4 ESD reversible blades set, 11 pcs.
Slotted/ Phillips/ TORX®/ hex/ ball end hex.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Colour-coded Wiha ChromTop® tips.
Blade length is adjustable from 18 - 90 mm.

Handle: SYSTEM 4 SoftFinish®-telescopic ESD handle.
ESD-safe (dissipative), surface resistance 10⁶ - 10⁹ ohms.
ClickStop ball clamp guarantees a secure hold and rapid blade exchange.

Extra: In a roll-up pouch made of ESD-safe material.

| Order-No. | Series | | | | |
|-----------|--------------|--|-----------|-----------|--|
| 31499 | 2691 T11 ESD | 5 | | | |
| | 2691ESD | SYSTEM 4 SoftFinish®-telescopic ESD handle | | | |
| ⓪ | ⓪ 269 | 1.5 - 3.0 | 2.0 - 3.5 | 2.5 - 4.0 | |
| ⊕ | ⊕ 269 | PH000 - PH00 PH0 - PH1 | | | |
| ⊗ | ⊗ 269 | T6 - T8 | T7 - T9 | | |
| ⊛ | ⊛ 269 | 1.5 - 1.5 | 2 - 2 | 2.5 - 2.5 | |

SYSTEM 4 ESD sets.



Telescopic



7000 EB16 ESD SYSTEM 4 ESD bit set, 16 pcs.
Mixed sets.

Handle: SYSTEM 4 SoftFinish®-telescopic ESD handle.
ESD-safe (dissipative), surface resistance 10⁶ - 10⁹ ohms.
Enables adjustable bit holder blade length.

Standards: DIN 3126, ISO 1173, style C 4.
IEC 61340-5-1.

Case: No danger to electronic components with use of ESD-safe materials.
Tough, space-saving metal box.

Application: Bit set suitable for smallest screws with electronic components.
Flexible working via adjustable blade length and rapid replacement of bit inserts.

| Order-No. | Series | | | | |
|-----------|---------------|--|--------|-------|-------|
| 33503 | 7000 EB16 ESD | 1 | | | |
| | 2691ESD | 1xSYSTEM 4 SoftFinish®-telescopic ESD handle | | | |
| | U759 00 | 1xSYSTEM 4 bit holder | | | |
| ⓪ | U750 | 1x2.0 | 1x3.0 | | |
| ⊕ | U751 | 1xPH000 | 1xPH00 | 1xPH0 | 1xPH1 |
| ⊗ | U757 | 1xT3 | 1xT4 | 1xT5 | 1xT6 |
| | | 1xT8 | | | |
| ⊛ | U753 | 1x0.9 | 1x1.3 | 1x1.5 | |



Telescopic



7000 EB26 ESD SYSTEM 4 ESD bit set, 26 pcs.
Mixed sets.

| Order-No. | Series | | | | |
|-----------|---------------|--|--------|-------|-------|
| 33848 | 7000 EB26 ESD | 1 | | | |
| | 2691ESD | 1xSYSTEM 4 SoftFinish®-telescopic ESD handle | | | |
| | U759 00 | 1xSYSTEM 4 bit holder | | | |
| ⓪ | U750 | 1x1.5 | 1x2.0 | 1x3.0 | 1x4.0 |
| ⊕ | U751 | 1xPH000 | 1xPH00 | 1xPH0 | 1xPH1 |
| ⊗ | U757 | 1xT3 | 1xT4 | 1xT5 | 1xT6 |
| | | 1xT7 | 1xT8 | 1xT9 | 1xT10 |
| ⊛ | U753 | 1x0.7 | 1x0.9 | 1x1.3 | 1x1.5 |
| | | 1x2.0 | 1x2.5 | 1x3.0 | 1x4.0 |