## HUBER+SUHNER® DATA SHEET Between Series Adapter: 31\_N-SMA-50-51/1--\_U

**(H)** 

## Description

Adaptor jack/jack

N-precision jack (female) / SMA-precision jack (female)

Interface standards

IEC 60169-16 MIL-STD-348A/402 CECC 22210

## **Technical Data**

## **Electrical Data**

 $\begin{array}{lll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 18 \ \text{GHz} \\ \text{VSWR} & \text{DC - 18 GHz} \\ & \leq 1.025 + 0.007 \ \text{f} \\ \text{Electrical Length} & 32.91 \ \text{mm} \ \text{+/- 0.1} \\ \end{array}$ 

**Mechanical Data** 

Number of matings 500 Weight 0.0316 kg

**Environmental Data** 

Operating Temperature 13 °C to 33 °C 2002/95/EC (RoHS) compliant

**Material Data** 

Piece Parts (N-precision) Material

Centre contact Copper Beryllium Alloy
Outer contact Stainless Steel
Body Stainless Steel

Insulator Air Dielectric - Bead - PPH

Piece Parts (SMA-precision) Material

Centre contact Copper Beryllium Alloy
Outer contact Copper Beryllium Alloy
Body Copper Beryllium Alloy

Insulator PFA / PTFE

**Related Documents** 

**Ordering Information** 

Single package 31\_N-SMA-50-51/1-\_UE

Surface Plating

Gold Plating (without Nickel underplating)

**Surface Plating** 

Gold Plating (without Nickel underplating)

SUCOPRO Plating SUCOPRO Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions** 

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000195562 O Issued: 11.08.08 Uncontrolled Copy Page 1/1