

Wiha SoftFinish® ESD.

For use on electrostatically sensitive components.



EPA

Wiha SoftFinish® ESD screwdrivers have a surface resistance of $10^6 - 10^9$ ohms.



The SoftFinish® ESD screwdrivers feature an impressive and ergonomic multi-component handle.

For work on electrostatically sensitive devices and assemblies, there is no better screwdriver than the Wiha SoftFinish® ESD, with integrated soft zone in the multi-component handle. The dissipative handle with a surface resistance of $10^6 - 10^9$ ohms discharges the electrostatic energy in a controlled manner to protect devices at risk from electrostatic discharge.

The ergonomic handle form was developed from the basis of extensive scientific investigations in cooperation with the Fraunhofer Institute. The result is a multi-component handle with a seamless outer form. Each hand size adapts perfectly to screwdriver, there are no pressure points while working and loading of the finger joints is minimised.



The hard handle core consists of impact resistant polypropylene. The thermoplastic elastomer handle provides for a pleasant, safe and slip-proof grip. The inseparable handle is connected to the core by a moulding process. The high-quality blade of chrome-vanadium- molybdenum steel is through hardened and mattechrome plated. The Wiha ChromTop® blade tip ensures a perfect fit in every screw head.

Wiha SoftFinish® ESD screwdrivers correspond to the internationally specified ESD standards IEC 61340-5-1.



Wiha SoftFinish® ESD.

- Dissipative handle designed to discharge uniformly, surface resistance $10^6 - 10^9$ ohms
- Meets ESD standard IEC 61340-5-1
- Ergonomic SoftFinish® multi-component handle guarantees comfortable work and optimised handling
- Blade made of high-quality CVM steel, through hardened and chrome plated
- Wiha ChromTop® blade tip ensure a perfect fit in every screw head



Safety Notice:

Wiha ESD screwdrivers are noninsulated, therefore not suitable for working on live parts.



For slotted, Phillips and Pozidriv screws.

For slotted, Phillips and Pozidriv screws.



302ESD SoftFinish® ESD slotted screwdriver. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⌀	↔	⊖	●	↔	↔	↔
08179	2.5	75	0.4	2.5	179	23	10
27150	3.0	100	0.5	3.0	204	23	10
27151	4.0	100	0.8	4.0	211	30	10
08182	5.5	125	1.0	5.5	236	30	10
08183	6.5	150	1.2	6.0	268	36	10



302ESD SoftFinish® ESD slotted screwdriver Stubby. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⌀	↔	⊖	●	↔	↔	↔
32151	4.0	25	0.8	4.0	81	34	10
32152	5.5	25	1.0	5.5	81	34	10
32153	6.5	25	1.2	6.5	81	34	10



311ESD SoftFinish® ESD Phillips screwdriver. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●	↔	↔	↔
08184	PH0	60	3.0	164	23	10
08185	PH1	80	4.5	191	30	10
08186	PH2	100	6.0	218	36	10



311ESD SoftFinish® ESD Phillips screwdriver Stubby. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●	↔	↔	↔
32154	PH1	25	4.5	81	34	10
32155	PH2	25	6.0	81	34	10



313ESD SoftFinish® ESD Pozidriv screwdriver. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●	↔	↔	↔
26928	PZ0	60	3.0	164	23	10
26929	PZ1	80	4.5	191	30	10



313ESD SoftFinish® ESD Pozidriv screwdriver Stubby. Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Surface resistance 10⁶ - 10⁹ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●	↔	↔	↔
32156	PZ1	25	4.5	81	34	10
32157	PZ2	25	6.0	81	34	10