

HUBER+SUHNER® DATA SHEET

Between Series Adapter: 33_MMPX-PC185-50-1/111_NE Rev.: E



Description

Adaptor plug/jack
MMPX plug (male) / PC 1.85 jack (female)

Interface standards
HUBER+SUHNER MMPX STD (Patent US 7.294.023)



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	65 GHz		
Frequency range	DC to 26.5 GHz	26.5 to 50 GHz	50 to 65 GHz
Return loss	≥ 22 dB	≥ 17 dB	≥ 17 dB

Mechanical Data

Number of matings	500
Weight	0.0031 kg

Environmental Data

Operating Temperature	-55 °C to 85 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (MMPX)

Centre contact	Copper Beryllium / Brass
Outer contact	Stainless Steel
Body	Stainless Steel
Insulator	PTFE

Surface Plating

SUCOPRO / Gold Plating

Piece Parts (PC 1.85)

Centre contact	Copper Beryllium / Brass
Outer contact	Bronze
Body	Bronze
Insulator	PTFE

Surface Plating

SUCOPRO / Gold Plating
SUCOPRO Plating
SUCOPRO Plating

Related Documents

Outline drawing	DOU-00063978
-----------------	--------------

Ordering Information

Single package	33_MMPX-PC185-50-1/111_NE
----------------	---------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions