












# Subracks – EuropacPRO Rugged

## REAR HORIZONTAL RAILS

### ORDER INFORMATION

		For indirect backplane fixing with insulation strip		For direct backplane fixing		For direct fixing of connectors in accordance with EN 60603-2 (DIN 41612)
 <p>06105074</p> <p>With HP markings from 28 HP, Al extrusion, anodised finish, conductive contact surface</p>		 <p>04400001</p> <p>"rugged" Type R-ST Standard</p>  <p>04400002</p> <p>"heavy" Type H-ST standard</p>  <p>06112005</p> <p>Al extrusion, anodised finish, conductive contact surface, with HP markings</p>  <p>06197011</p> <p>Al extrusion, anodised finish, conductive contact surface, with HP markings</p>	 <p>04400002</p> <p>"rugged" Type R-VT recessed installation</p>  <p>04400003</p> <p>"heavy" Type H-VT recessed installation</p>  <p>06112006</p> <p>Al extrusion, anodised finish, conductive contact surface, with HP markings</p>  <p>06197013</p> <p>Al extrusion, anodised finish, conductive contact surface, with HP markings</p>	 <p>04400003</p> <p>"heavy" Type H-MZ with Z-rail</p>  <p>06197015</p> <p>Al extrusion, anodised finish, conductive contact surface, with HP markings</p>		
Usable length HP	Length mm	1 piece (SPQ 10) <sup>1)</sup>	1 piece (SPQ 10) <sup>1)</sup>	1 piece (SPQ 10) <sup>1)</sup>	1 piece (SPQ 10) <sup>1)</sup>	1 piece (SPQ 10) <sup>1)</sup>
20	106.68	34566-520	<b>34560-520</b>	34566-720	<b>34560-720</b>	<b>34560-920</b>
28	147.32	34566-528	<b>34560-528</b>	34566-728	<b>34560-728</b>	<b>34560-928</b>
40	208.28	34566-540	<b>34560-540</b>	34566-740	<b>34560-740</b>	<b>34560-940</b>
42	218.44	34566-542	<b>34560-542</b>	34566-742	<b>34560-742</b>	<b>34560-942</b>
63	325.12	34566-563	<b>34560-563</b>	34566-763	<b>34560-763</b>	<b>34560-963</b>
84	431.80	34566-584	<b>34560-584</b>	34566-784	<b>34560-784</b>	<b>34560-984</b>
–	1000	34566-501	<b>34560-501</b>	34566-701	<b>34560-701</b>	–
Insulation strips see page		6.104	6.104	–	–	–
Threaded inserts see page		6.104	6.104	6.104	6.104	6.104
Fixing material kits see page		6.103	6.103	6.103	6.103	6.103

1) SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple  
 "heavy" load > 7.5 kg; "rugged" load > 15 kg;

### NOTE

- 1000 mm version without M4 thread to front, without printing and without notch for 19"-bracket
- EMC gasket see page 6.56
- For further horizontal rails see page 6.29