Wiha SoftFinish® electric slimFix.

The convenient slim solution for electrical applications.



Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.

The high quality blade insulation is moulded directly onto the blade and therefore guarantees safety when working on live equipment up to 1,500 V DC/ 1,000 V AC. To maintain this safety, each screwdriver of the SoftFinish® electric series is individually tested in a water bath at 10,000 Volts according to IEC 60900:2012.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications.



slimTECHNOLOGY: Up to 33% reduction of the bit diameter in the critical working area allows effortless access to low-lying fastening/spring elements.





- Unlimited access
- Blades up to 33% narrower due to integrated insulation
- Tool for spring clips (wedgeprofiled output geometry)









SoftFinish® electric slimFix sets.



NEW

3201 K6 01 SoftFinish® electric slimFix slotted/Phillips/Pozidriv Xeno screwdriver set, 6-pcs.

Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish.

Protective insulation moulded directly onto the blade and completely

integrated into the blade in the lower area.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. Extra: The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

	opining dictricate to be reached and manipulated.						
Order-No.	Series						
38362	3201 K6 (1					
1	3201	3.5x100	4.0x100	5.5x125			
⊕	3211	PH1x80	PH2x100				
₩	3281	SL/PZ2 x 100					



3251 K6 SoftFi

SoftFinish® electric slimFix TORX® screwdriver set, 6-pcs.

Individually tested protective insulation 1,000 V AC, VDE and GS $\,$

tested.

Blade: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. Extra: The integrated protective insulation enables low-lying fastening

elements to be reached and manipulated.

	elements to be reached and manipulated.						
Order-No.	Series						
36558	3251 K6				1		
	325	T8x60	T9x60				
	3251	T10x100	T15x100	T20x100	T25x125		

Displays.



3211 VB Display SoftFinish® electric slimFix.

Card display with 18 pcs.

Size: 28 x 13 x 36 cm (WxDxH).

Order-No.	Series			_	=	
35559	3211 VB			1		
Φ	3201	3x3.5	3x4.0	3x5.5	3x6.5	
•	3211	3xPH1	3xPH2			





Display SoftFinish® electric slimFix.
Card display with 18 pcs.

