

Torque screwdriver TorqueVario®-S ESD
Variable torque limit settings (36851) 0,04-0,46
Nm, 4 mm



Wiha Werkzeuge GmbH
Obertalstraße 3-7
78136 Schonach

E-Mail: info.de@wiha.com
Tel.: +49 (0)7722 959-0



Article No.: 36851

GTIN: 4010995368517

Unit: Piece

Meets your requirements: A variably settable torque covers a large application area.

Lowers your costs: Electrostatically conductive tools protect electronic components from damage.

Protects your health: With the patented SoftFinish® handle design, ensuring work is kind to hands and muscles. Recommended by doctors and therapists at German Campaign for Healthier Backs.

Increases your efficiency: The correct torque avoids damaging material and no follow-up work is necessary.

Standards: IEC 61340-5-1.DIN EN ISO 6789.

Application: For ESD applications where recommended torque settings are important. Use in combination with a Wiha Torque ESD interchangeable blade.

Handle_length 127 mm

Handle diameter 23 mm

Weight 138 g

Nm 0,04-0,46 Nm

Tolerance 10% %

Hex 4 mm

Serie 2.882

Anwendungsszenarien For ESD applications where recommended torque settings are important. Use in combination with a Wiha Torque ESD interchangeable blade.

Customs tariff number 82054000

Product group 36851