

LV HRC fuse element, NH000, In: 25 A, gG, Un AC: 500 V, Un DC: 250 V, Combined indicator, Insulated grip lugs



| Model | |
|--|---------------------------------|
| Product brand name | SENTRON |
| Product designation | LV HRC fuse link |
| Design of the product | With blade contacts |
| Design of an identification indicator | Combination alarms |
| Design of the switching contact | Non-corroding, silver-plated |
| Design of the fuse link | LV HRC fuse link |
| General technical data | |
| Size of fuse system / acc. to DIN EN 60269-1 | NH000 |
| Operating class of the fuse link | gG |
| circuit-breaker / Design | 3NA6 |
| Supply voltage | |
| • at AC / rated value | 500 V |
| • at DC | 250 V |
| Protection class | |
| Protection class IP | IP20, with connected conductors |
| Switching capacity | |
| Switching capacity current | |

- at DC / acc. to IEC 60947-2 / rated value 25 kA
- acc. to IEC 60947-2 / rated value 120 kA

Dissipation

| | |
|---|-------|
| Power loss [W] | 2.3 W |
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 2.3 W |

Electricity

| | |
|---|---------------------|
| Tripping residual / rated value / derated current / at 40 Cel | 23.75 A |
| Current / at AC / rated value | 25 A |
| Diken-export / Let-through energy | DE_3NA_00_500_gG_25 |

Mechanical Design

| | |
|--------------------|--------------------------|
| Width | |
| • of the enclosure | 21 mm |
| Mounting position | Any, preferably vertical |
| Net weight | 132 g |

Environmental conditions

| | |
|------------------------|-------------------------------------|
| Ambient temperature | |
| • minimum | -5 °C |
| • maximum | 40 °C |
| • during storage | Air humidity 90% at 20 °C |
| Environmental category | -20 to +50 at 95% relative humidity |

Certificates

| | |
|--------------------------|---|
| Reference code | |
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

General Product Approval

Declaration of Conformity

Test Certificates



KEMA



VDE



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

Shipping Approval

other

[Miscellaneous](#)



GL

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA6810>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NA6810>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6810

CAX-Online-Generator

<http://www.siemens.com/cax>


Tender specifications

<http://www.siemens.com/specifications>



1

-F1



2