

Spring flap for 3RW52 with cutout for HMI module Standard



Product category	Enclosure components
Product designation	Hinged cover
Design of the product	With cutout for HMI module Standard
Manufacturer's article number	
<ul style="list-style-type: none"> • of soft starter 	3RW51
<ul style="list-style-type: none"> • of soft starter 	3RW52
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during storage and transport 	-40 ... +80 °C

General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping
--------------------------	---------------------------	-------------------	-------------------



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5950-0GL40>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5950-0GL40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5950-0GL40&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GL40/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5950-0GL40&objecttype=14&gridview=view1>

last modified:

04/03/2019