



AS-INTERFACE MOUNTING PLATE K60 FOR COMPACT MODULE K60,  
MOUNT. ON RAIL FOR 2 RIBBON CABLE,  
AS-INTERFACE CABLE (YELLOW) AND AS-INTERFACE CABLE 24 V (BLACK)

General technical data:		
Type of device		accessories digital I/O modules for operation in the field, IP67 - K60
Design of the product		K60 mounting plate for standard rail mounting
Note		For the previous version of the 3RK1901-0CB00 standard rail mounting it is also possible to order the standard rail adapter as a spare part: 3RX1660-0B. This adapter is not required for the new 3RK1901-0CB01 version.
Note 1		additional seals are required only when the flat cables end in the module (3RK1 902-0AR00)
Connections:		
connection		insulation piercing method for AS-Interface flat cable
Connection system		insulation piercing method for AS-Interface flat cable
Mechanical design:		
Type of mounting		for standard rail mounting
Ambient conditions:		
ambient temperature	°C	-25 ... +85
degree of protection		IP67 with screw-mounted K60 compact module
Certificates/approvals:		

## General Product Approval



CSA



GOST



UL

## Shipping Approval



ABS



DNV



PRS



RMRS

## other

[Confirmation](#)

[Declaration of  
Conformity](#)

[Environmental  
Confirmations](#)

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

### Cax online generator


<http://www.siemens.com/cax>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3RK1901-0CB01/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RK1901-0CB01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RK1901-0CB01)



last change:

Mar 13, 2013