4-2271101-1 ACTIVE

TE Internal #: 4-2271101-1

Solder D-Sub Connectors, Receptacle, 36 Position, .05 in [1.27 mm]

Centerline, Printed Circuit Board, -67 – 221 °F [-55 – 105 °C]

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > Solder D-Sub Connectors











Connector & Housing Type: Receptacle

Number of Positions: 36

Centerline (Pitch): 1.27 mm [.05 in]

Connector & Contact Terminates To: Printed Circuit Board

Contact Current Rating (Max): 1 A

Features

Product Type Features

Shell Type	Full Metal Shell
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	36	

Body Features

Color	Black
Shell Material	Steel

Contact Features

Contact Type	Pin
Contact Mating Area Plating Thickness	.3 μm[11.8 μin]
Contact Mating Area Plating Material	Gold
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy



Contact Current Rating (Max)	1 A
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
PCB Mount Retention Type	Retention Leg
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	1.27 mm[.05 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards	
Insert Flammability Rating	UL 94V-0
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought

















Documents

Product Drawings
SCSI .050 REC ASS'Y 36P PB-FRE

English

CAD Files
3D PDF

3D

Customer View Model ENG_CVM_CVM_4-2271101-1_A.2d_dxf.zip

Solder D-Sub Connectors, Receptacle, 36 Position, .05 in [1.27 mm] Centerline, Printed Circuit Board, -67 – 221 °F [-55 – 105 °C]



English

Customer View Model

ENG_CVM_CVM_4-2271101-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-2271101-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English