




 DUCATI energia	CAPACITOR for POWER ELECTRONIC - GENERAL PURPOSE APPLICATIONS -	GP84 Cn = 300μF Urms= 330V Part. Number: 416.84.3758
---	--	---

GP 84

AC / DC - Power electronic Capacitors

CHARACTERISTICS

Rated Capacitance (Cn)	300	μF
Capacitance Tolerance	±5%	
Rated RMS Voltage (Urms)	330	V
Max. AC Voltage (Un ac)	470	V
Rated DC Voltage (Un)	600	V
Maximum Current (Imax) @ θ _{MAX}	75	A
Maximum Current (Imax) @ 45°C	90	A
Self-inductance (L _{ESR})	< 230	nH
Equivalent series resistance (R _{ESR})	< 4.0	mΩ
Typical tan d (10 ⁻⁴)	7,0	(Measure @ 50Hz)
Thermal resistance natural cooling (R _{THC})	1,0	°C/W
Filler material: Polyurethane Resin PPM film Dielectric - self healing technology.		
Over pressure safety device		
Aluminium case, M12 fixing stud.		
Weight	≤ 1450	g
Dimension Ø x H	85 x 220	mm



MAXIMUM RATINGS

Over voltage	1.1 Un	8hours/day
Non-recurrent surge voltage (Us)	1150	V
Maximum peak current (I _{PK})	135	A
Max. Voltage raise of rise (dV/dt)	60	V/μs
Maximum surge current (Is)	21	kA
Maximum Fault current - UL810	10.000	A
Max .Fixing Torque for terminals (*)	6	Nm
Max .Fixing Torque for M12 stud	10	Nm

(*) To avoid breaking, complete the tightening of the nuts using two wrenches.

TEST DATA

DC Test voltage terminal to terminal	1,5xUnx 10s	Vdc
AC test voltage terminal to case	3kV x 10s	Vac 50Hz

CLIMATIC CATEGORY

Min.operating temperature (θ _{MIN})	-25	°C
Max. operating temperature (θ _{MAX})	+70	°C
Storage temperature	-40 +85	°C
Altitude maximum	2000m	a.s.l.

Failure quota	300/10 ⁹
Expected life (Ln)	100.000 h @ 330Vac / 50Hz

STANDARDS

EN 61071-1/2
UL - CSA approval

**Total elongation is about 15 mm after the overpressure disconnector release.
Don't use rigid connections.**

Release	Date	Description	Technician
-	22/02/12	First issue: equivalent to 416843754, but with new plastic cover	A. G.