

**Screwdriver SoftFinish® electric**



**Hex nut driver**

322

Order-No.	⊖	↔	mm	↔	⊕	🔋
00853	4	125	236	30	10,2	10
00855	5	125	236	30	11,2	10
00856	5,5	125	236	30	11,2	10
00857	6	125	236	30	12,2	10
00858	7	125	243	36	14,5	10
00859	8	125	243	36	15,2	10
00860	9	125	243	36	16,0	10
00861	10	125	243	36	17,2	10
00862	11	125	243	41	19,2	10
00863	12	125	243	41	20,2	10
00864	13	125	243	41	22,2	10
00865	14	125	243	41	23,2	10
00866	15	125	243	41	25,2	10
00867	16	125	243	41	25,2	10
00868	17	125	243	41	27,2	10

Manufactured acc. to IEC 60900.

**Fine screwdriver PicoFinish electric**



**Slotted**

2270P

Order-No.	⊖	↔	●	mm	↔	🔋
42374	1,5	50	2,0	152	18	10
42375	2,0	50	2,0	152	18	10
42376	2,5	65	2,5	167	18	10
42377	3	65	3	167	18	10
42471	3,5	65	3,5	167	18	10

**Phillips**

2271P

Order-No.	⊕	↔	●	mm	↔	🔋
42379	PH00	50	2	152	18	10
42378	PH0	65	3	167	18	10
42380	PH1	65	4	167	18	10

**Voltage tester SoftFinish® single-pole, 110-250 volts**



**Slotted transparent, with push-on clip**

255-11

Order-No.	⊖	↔	⊖	mm	↔	SB	🔋
34745	3,0	60	0,5	140	19		10
35378	3,0	60	0,5	140	19	x	5

Tested according to DIN 57680-6, GS, CE compliant.

**Single-pole, explosion-protected, non-contact volt detector, 12-1,000 V AC**



**Includes two AAA batteries**

25513

Order-No.	●	↔	mm	🔋
43797	2	28,5	150	

**Single-pole, non-contact volt detector, 90-1,000 VAC**



**Includes two AAA batteries**

25514

Order-No.	●	↔	mm	🔋
43798	2	28,5	150	5

**Voltage tester 220-250 volts**



**Slotted transparent, with push-on clip**

255-3

Order-No.	⊖	↔	mm	↔	SB	🔋
05271	3,0	60	140	15		10
32201	3,0	60	140	15	x	5

**Voltage tester 150-250 volts**



**Slotted black, with push-on clip**

255-7

Order-No.	⊖	↔	mm	↔	SB	🔋
00456	3,0	60	160	17		10
31771	3,0	60	160	17	x	1