



**WIRING COLOR:**

E: Yellow/Green  
N: Blue  
L: Brown

LENGED ON CORD: (四字)

I-SHENG KSIS <VDE> KEMA-KEUR 403 403 403 <OVE> △ CEBC 809 NF-USE  
1353 IEMMEQU H05VV-F 3G 0.75mm<sup>2</sup> 60227 IEC 53 RVV 300/500V A041481  
3ASL/75 4V-75 V-75(75°C) 250/440V ORDINARY DUTY Q88228 -LF- CE

| No | BOM ITEM               | Q' TY  | P/N      |
|----|------------------------|--------|----------|
| 1  | SP023 INSERT           | 1 pcs  | MB023012 |
| 2  | PVC 50P (SP-022)       | 29.7 g | RPP05012 |
| 3  | KPR-14 BLADE           | 3 pcs  | BBB14000 |
| 4  | IS-14 INNER BODY       | 1 pcs  | MI014000 |
| 5  | PVC 50P (IS-14)        | 14.3 g | RPP05012 |
| 6  | PE TIE (BLACK, 6 inch) | 1 pcs  | KBBPE115 |

|        |      |  |         |               |         |
|--------|------|--|---------|---------------|---------|
| CABLE  |      | H05VV-F 3G 0.75 DENT PRINT CT-12 (BLACK) |         |               |         |
| PLUG   |      | SP-022 + IS-14                           | LENGTH  | 1980          | UNIT mm |
| CLIENT | NAME | Elfa Distrelec                           | N/W     |               | UNIT kg |
|        | P/N  | 43-526-44                                | KS DWG  | SR-12090041-9 | VER. A  |
|        |      | Design. by                               | 李润新 1/2 |               |         |
|        |      | Review. by                               | 李俊强 1/1 |               |         |
|        |      | Approval. by                             | 李润新     |               |         |
|        |      | <b>Maxxtro®</b>                          |         |               |         |
|        |      | V24                                      | 6B3016  | 12            | 200 00  |