



WIRING COLOR:
 E: Yellow/Green
 N: Blue
 L: Brown

LENGED ON CORD: (四字)
 I-SHENG KSIS <VDE> KEMA-KEUR +0+0+0 <0VE> △ CEBC 809 S(D)(N)(H)
 NF-USE 1353 IEMMEQU H05VV-F 3G 0.75mm² 60227 IEC 53 RVV 300/500V
 A041481 3ASL/75 4V-75 V-75(75°C) 250/440V ORDINARY DUTY Q88228 -LF- CE

No	BOM ITEM	Q' TY	P/N
1	SP-029 INSERT	1 pcs	MB029012
2	PVC 50P (SP-029)	30 g	RPP05012
3	KPR-14 TERMINAL	3 pcs	BBB14000
4	IS-14 INNER BODY	1 pcs	MI014000
5	PVC 50P (IS-14)	14.3 g	RPP05012
6	PE TIE (BLACK, 6 inch)	1 pcs	KBBPE115

CABLE	H05VV-F 3G 0.75 DENT PRINT CT-12 (BLACK)			
PLUG	SP-029 + IS-14	LENGTH	1800	UNIT mm
CLIENT	NAME	Elfa	N/W	UNIT kg
	P/N	43-526-50	KS DWG	SR-1210151-3 VER. A
Maxxtro®			Design. by	TESS
			Review. by	汪華高
			Approval. by	周家榮
V91 6B3016 12 180 00				