

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0445600024](#)  
**Status:** **Active**  
**Overview:** [Magnetic and Modular Jacks/Plugs](#)  
**Description:** [Modular Jack, Right-Angle, Low Profile, Shielded, 8/8, 4 Ports](#)

**Documents:**

|  |  |
|--|--|
| <a href="#">Drawing (PDF)</a>                                | <a href="#">Packaging Specification PK-44560-005-001 (PDF)</a> |
| <a href="#">3D Model</a>                                     | <a href="#">Test Summary TS-44560-003-001 (PDF)</a>            |
| <a href="#">3D Model (PDF)</a>                               | <a href="#">RoHS Certificate of Compliance (PDF)</a>           |
| <a href="#">Product Specification PS-44560-003-001 (PDF)</a> |  |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E107635 |

**General**

|                           |  |
|---------------------------|--|
| Product Family            | Modular Jacks/Plugs                              |
| Series                    | <a href="#">44560</a>                            |
| Comments                  | Bezel Shield                                     |
| Component Type            | PCB Jack   |
| Magnetic                  | No   |
| Overview                  | <a href="#">Magnetic and Modular Jacks/Plugs</a> |
| Performance Category      | 5, 5e  |
| Power over Ethernet (PoE) | N/A  |
| Product Name              | Modular Jack 8/8, RJ45                           |
| UPC                       | 756054374412                                     |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 500                            |
| Flammability                   | 94V-0                          |
| Inverted / Top Latch           | No                             |
| Jack Height                    | 11.23mm                        |
| Lightpipes/LEDs                | None                           |
| Material - Metal               | Brass, Phosphor Bronze         |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 12.057/g                       |
| Orientation                    | Right Angle (Side Entry)       |
| PCB Retention                  | Yes                            |
| PCB Thickness - Recommended    | 1.60mm                         |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 1.02mm                         |
| Pitch - Termination Interface  | 1.27mm                         |
| Plating min - Mating           | 1.270µm                        |
| Plating min - Termination      | 2.540µm                        |
| Port Configuration             | 1x4                            |
| Positions / Loaded Contacts    | 8/8                            |
| Surface Mount Compatible (SMC) | No                             |
| Temperature Range - Operating  | -40° to +85°C                  |
| Termination Interface: Style   | Through Hole                   |
| Wire/Cable Type                | N/A                            |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 1.5A |
| Shielded                      | Yes  |



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Not Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[44560 Series](#)

**Mates With**

[FCC 68 Plugs](#)

Voltage - Maximum 150V

**Solder Process Data**

Duration at Max. Process Temperature (seconds) 005  
Lead-free Process Capability WAVE  
Max. Cycles at Max. Process Temperature 001  
Process Temperature max. C 260

**Material Info**

**Reference - Drawing Numbers**

Packaging Specification PK-44560-005-001  
Product Specification PS-44560-003-001  
Sales Drawing RSD-44560-001-001, SD-44560-001-001  
Test Summary TS-44560-003-001

This document was generated on 11/09/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**