
## KEMET Part Number: C44PKGR6150AASJ Not for New Design



## C44P, Film, Metallized Polypropylene, AC Filter, 150 uF, 5%, 440 VAC, 1000 VDC



Dimensions	
D	65mm +/-0.5mm
L	247mm +/-2mm
W	18mm +/-1mm
S	28mm +/-1mm
W1	40mm +/-1mm

Packaging Specifications		
Mounting:	Bolt - M12x16	
Packaging:	Bulk, Bag	

General Information	
Series:	C44P
Dielectric:	Metallized Polypropylene
Style:	Can
Features:	Single Phase PFC
RoHS:	With Exemptions
REACH:	SVHC (Pb – CAS 7439-92-1)
SCIP Number:	cc1c1ec4-db9e-4815-b26b- e8a34ddfb776
Lead:	Threaded Studs M10
AEC-Q200:	No
Component Weight:	1000 g
Miscellaneous:	Thermal Resistance = 3.5 C/W.

Specifications		
Capacitance:	150 uF	
Capacitance Tolerance:	5%	
Voltage AC:	440 VAC	
Voltage DC:	1000 VDC	
Temperature Range:	-25/+70°C	
Rated Temperature:	70°C	
Max dV/dt:	20 V/us	
Resistance:	2.8 mOhms (10kHz)	
Ripple Current:	45 Amps (10kHz 40C)	
Inductance:	160 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

