# 5-520315-8 ACTIVE

#### TRIO-MATE

TE Internal #: 5-520315-8

TRIO-MATE, FFC Connectors, Connector Assembly, Wire-to-Board, 8 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FFC Connectors



FFC Connector Product Type: Connector Assembly

Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 2.54 mm [.1 in]

Number of Rows: 1

### **Features**

### **Product Type Features**

Connector & Housing Type	Receptacle
FFC Connector Product Type	Connector Assembly
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Insertion Force Type	Low Insertion Force (LIF)
Configuration Features	
Number of Positions	8
Number of Rows	1
PCB Mount Orientation	Vertical
PCB Mount Orientation  Contact Features	Vertical
	Vertical
Contact Features	
Contact Features  Contact Mating Area Plating Material	Tin
Contact Features  Contact Mating Area Plating Material  Contact Mating Area Plating Material Finish	Tin Bright
Contact Features  Contact Mating Area Plating Material  Contact Mating Area Plating Material Finish  PCB Contact Termination Area Plating Material	Tin Bright Tin
Contact Features  Contact Mating Area Plating Material  Contact Mating Area Plating Material Finish  PCB Contact Termination Area Plating Material  Contact Base Material	Tin Bright Tin Phosphor Bronze

3.56 mm[.14 in]

Termination Post & Tail Length



Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
PCB Mount Alignment	Without
PCB Mount Retention	With
PCB Mount Retention Type	Z Bend
Mating Retention	Without
Mating Alignment	With
Panel Mount Feature	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	2.54 mm[.1 in]
FFC Cable Entry	Vertical
Housing Color	Black
Dimensions	
PCB Thickness (Recommended)	1.57 mm[.062 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	660
Packaging Method	Tray

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### Compatible Parts



### Also in the Series | TRIO-MATE



## Customers Also Bought



















### **Documents**

### **Product Drawings**

**8 POS TRIO MATE ASSY VERT** 

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-520315-8\_S.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-520315-8\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-520315-8\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

Trio-Mate Flat Flexible Discrete Circuit .100 Connectors

English

**Application Specification** 

Japanese

**Application Specification** 

English

**Product Environmental Compliance** 

TRIO-MATE, FFC Connectors, Connector Assembly, Wire-to-Board, 8 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray



**Product Compliance** 

English

**Product Compliance** 

English