



from M50x1,5: with o-ring

BN 22055

Cable glands

with metric thread

Stainless steel 1.4305

- Dome nut: stainless steel 1.4305
- Lamellar insert: polyamide PA 6 V-2
- Sealing ring: polychloroprene-Nitrile rubber CR/NBR
- Gland body: stainless steel 1.4305
- O-ring: Nitrile rubber NBR
- Connecting thread: metric, as per EN 60423
- Integrated anchorage, protection against twisting, wide sealing and clamping range, easy-to-install
- Temperature range: -20 °C / +100 °C (dynamic)
- Temperature range: -40 °C / +100 °C (static, short term)
- Protection grade: IP68, IP69K (tested for M12-M25, M50 and M63)



Test standard: UL 514B
UL/CSA-File: E140310

Article#	d ₁	Clamping range	SW1	SW2	L	L ₁	Code
3692578	M12x1,5	3-6	14	14	5	25	50.612ES
3692579	M16x1,5	5-9	17	17	5	30	50.616ES
3692577	M20x1,5	9-13	22	22	6	33,5	50.620ES
3692580	M25x1,5	11-16	27	27	7	36,5	50.625ES
3692583	M32x1,5	14-20	34	34	8	38	50.632ES
3692584	M40x1,5	19-27	43	43	8	41	50.640ES
3692581	M50x1,5	24-35	55	55	9	49,5	50.650ES
3692582	M63x1,5	32-42	65	65	10	52,5	50.663ES