
## KEMET Part Number: R523R415050P0K

(523R415050P0K)



R52 310 VAC MINI, Film, Metallized Polypropylene, Automotive Safety, 1.5 uF, 10%, 310 VAC (X2), 630 VDC, 110°C, Lead Spacing = 27.5mm



Dimensions	
L	32mm +0.3/-0.7mm
Н	20mm +0.1/-0.7mm
Т	11mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	336

General Information		
Series:	R52 310 VAC MINI	
Dielectric:	Metallized Polypropylene	
Style:	Radial	
Features:	EMI Safety	
RoHS:	Yes	
Lead:	Wire Leads	
Safety Class:	X2	
Qualifications:	ENEC, UL, cUL, CQC, AEC- Q200	
AEC-Q200:	Yes	
THB Performance:	Yes	
Component Weight:	8.012 g	

Specifications		
Capacitance:	1.5 uF	
Capacitance Tolerance:	10%	
Voltage AC:	310 VAC (X2)	
Voltage DC:	630 VDC	
Temperature Range:	-40/+110°C	
Rated Temperature:	110°C	
Dissipation Factor:	0.2% 1KHz	
Insulation Resistance:	45 GOhms	
Max dV/dt:	150 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

