



Silicone Servolitze twisted 3-wire

Product detail view Article number: 54050 - SILICON LITZE



. JR / Graupn, 0.14 mm², 72 x 0.05 mm highly flexible, 5 m, brown, red, orange - Made in Germany - max .: 48 V, 3 A

Technical specifications:

Category:

Servolitzen, meter, 5m | JR, university, Graupner packed,

silicone isolated copper flex wire, twisted | JR color, 3 x 0.14 mm, 72 x 0.05 mm, - Made in Germany - max .: 48 V, 3 A

Silikon-, Servolitzen - Vogel Kabel












Silicone servo wire

Câble silicone pour les servos

Cable silicona para los servos

5 m 100 m
Blister Rolle

54050	54060	3x 0,14 mm² AWG 26	Silikon hochflexibel	72 x 0,05 - Ø 1,2 mm / 2,5 mm 48 V - 3,0 A	JR/Graupner braun/rot/orange	
54053	54063	3x 0,25 mm² AWG 24	Silikon hochflexibel	130 x 0,05 - Ø 1,4 mm / 2,9 mm 48 V - 5,0 A	JR/Graupner braun/rot/orange	
54056	54066	3x 0,35 mm² AWG 22	Silikon hochflexibel	88 x 0,07 - Ø 1,5 mm / 3,2 mm 48 V - 8,0 A	JR/Graupner braun/rot/orange	
54057	54067	3x 0,35 mm² AWG 22	Silikon hochflexibel	88 x 0,07 - Ø 1,5 mm / 3,2 mm 48 V - 8,0 A	Futaba schwarz/rot/weiß	
54058	54068	3x 0,50 mm² AWG 20	Silikon hochflexibel	270 x 0,05 - Ø 1,8 mm / 3,7 mm 48 V - 12,0 A	JR/Graupner braun/rot/orange	
54059	54069	3x 0,50 mm² AWG 20	Silikon hochflexibel	270 x 0,05 - Ø 1,8 mm / 3,7 mm 48 V - 12,0 A	Futaba schwarz/rot/weiß	
54070	54071	2x 0,50 mm² +1x 0,14 mm²	Silikon hochflexibel	130 x 0,07 - Ø 1,8 mm 72 x 0,05 - Ø 1,2 mm / 3,9 mm	Futaba schwarz/rot/weiß	
54075	54076	2x 1,0 mm² +1x 0,25 mm²	Silikon hochflexibel	266 x 0,07 - Ø 2,3 mm 66 x 0,07 - Ø 1,2 mm / 4,8 mm	Futaba schwarz/rot/weiß	
54054	54064	3x 0,25 mm² AWG 24	Silikon hochflexibel	130 x 0,05 - Ø 1,4 mm x 3,2 mm 48 V - 5,0 A	JR/Graupner+Futaba rot mit schwarzer Markierung/rot/rot mit Schriftzug "orange"	

Litzendaten:	Querschnitt:	0,14 mm²	0,25 mm²	0,35mm²	0,50 mm²
(weitere Daten auf den Seiten 85 und 86)	Innenwiderstand Ω/1 m:	0,125	0,065	0,056	0,034
	Spitzenstrom (A) kurzzeitig:	6,1	10	15	21

71424kt



Buchsenkontakt für alle EXPERT- und PREMIUM-Kabel.
Dieser hochwertige Kontakt ist in jedem Jumbo und Space Shuttle zu finden.
Female connector contact for all EXPERT and PREMIUM cables
You'll find this high-quality contact in every jumbo and in every Space Shuttle.
Contact femelle pour tous les câbles d'EXPERT et PREMIUM
Ce contact de haute qualité peut être trouvé dans chaque navette Jumbo et de l'espace.
Contacto hembra para todos los cables de EXPERT y PREMIUM
Este contacto de alta calidad se pueden encontrar en cada traslado Jumbo y del Espacio.



48210kt



Stiftkontakt für alle Expert- und Premium-Kabel bestehen aus Vollmetall.
Pins for all EXPERT and PREMIUM cables are made of solid metal.
Pin pour tous les EXPERT et le câble PREMIUM en métal solide.
Pin para todos EXPERT y cable PREMIUM hecha de metal sólido.

