

Remote control switch with 1 NO contact, and 1 NC Contact for 230 V AC, 400V 16A Control 230 V AC



Model	
Product brand name	SETRON
Product designation	Remote control switch
Latching relay design	Mechanical switch
General technical data	
Electrical endurance (switching cycles)	50 000
Pulse duration / minimum	50 ms
Galvanic isolation / between magnet coil and contact	Yes
Switching voltage / of the contacts / at AC / minimum	10 V
Switching current / at AC / per contact / minimum	100 mA
Power loss [V·A] / of magnet coil / with pulse / rated value	7 V·A
Voltage	
Type of voltage	AC
Continuous voltage fuse version	Yes
Surge voltage resistance / rated value	4 kV
Supply voltage	250 V
Supply voltage / minimum	250 V

Protection class	
Protection class IP	IP20, with connected conductors
Switching capacity	
Switching capacity apparent power	
<ul style="list-style-type: none"> • for fluorescent lamp load with DUO circuit 	900 V·A
<ul style="list-style-type: none"> • for fluorescent lamp load with parallel compensation 	400 V·A
<ul style="list-style-type: none"> • for uncompensated fluorescent lamp load 	500 V·A
Switching capacity current	
<ul style="list-style-type: none"> • at cos phi 0.6 	16 A
<ul style="list-style-type: none"> • Rated value 	16 A
Switching capacity active power / with filament lamp load	2 000 W
Dissipation	
Power loss [W]	
<ul style="list-style-type: none"> • at 16 A / per contact / rated value 	1.2 W
<ul style="list-style-type: none"> • of magnet coil / with pulse / rated value 	4.5 W
Switching current	
<ul style="list-style-type: none"> • with glow lamp load / with 5TT4 920 compensating capacitor 	25 mA
<ul style="list-style-type: none"> • with glow lamp load 	5 mA
Control current	
Type of voltage	
<ul style="list-style-type: none"> • of control voltage_1 	AC
Control voltage	
<ul style="list-style-type: none"> • _1 / initial value 	184 V
<ul style="list-style-type: none"> • _1 / Full-scale value 	253 V
<ul style="list-style-type: none"> • _1 / setpoint 	230 V
Control voltage frequency	
<ul style="list-style-type: none"> • _1 / initial value 	50 Hz
<ul style="list-style-type: none"> • _1 / Full-scale value 	50 Hz
Operating range factor control supply voltage rated value / at AC / at 50 Hz	
<ul style="list-style-type: none"> • initial value 	0.8
<ul style="list-style-type: none"> • Full-scale value 	1.1
Product details	
Product component / Switch position indicator	Yes
Product function	
Product function / direct operation	Yes
Number	

Number of terminals	6
Number of NC contacts	1
Number of NO contacts	1
Number of CO contacts	0

Connections

Connectable conductor cross-section	
<ul style="list-style-type: none"> • for flexible conductor / with core end processing <ul style="list-style-type: none"> — minimum 1 mm² — maximum 6 mm² • for rigid conductor <ul style="list-style-type: none"> — minimum 1 mm² — maximum 6 mm² 	
Tightening torque / with screw-type terminals	
<ul style="list-style-type: none"> • minimum 0.8 N·m • maximum 1 N·m 	



Mechanical Design

Width of opening / of the contacts	1.2 mm
Mounting height	90 mm
Mounting position	any
Installation depth	70 mm
Number of width units	1
Mounting type	DIN rail
Required spacing / for live parts	6 mm
Net weight	143 g

Environmental conditions

Ambient temperature	
<ul style="list-style-type: none"> • minimum -10 °C • maximum 40 °C 	

Certificates

General Product Approval	Declaration of Con- formity	Test Certificates
 VDE	 EG-Konf.	Miscellaneous Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4105-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/5TT4105-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4105-0

CAX-Online-Generator
<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>

