TT41NGRA1 - ACTIVE

Alcoswitch

TE Internal #: 6-1437562-9 Toggle Switches, Four Pole - Double Throw Configuration (Pole-Throw), Sealed, Gold, Gold, Terminal Seal (Epoxy), Baton Short, On None On, .4 A, 20 VDC

View on TE.com >

Relays, Contactors & Switches > Switches > Toggle Switches



Configuration (Pole-Throw): Four Pole - Double Throw Sealed Toggle Switch: Yes Contact Base Material: Gold Switch Contact Plating Material: Gold Process Sealed: No

Features

Product Type Features

Product Type	Switch
Sealed Toggle Switch	Yes
Toggle Style	Baton Short



Toggle Switch Type	Toggle
Toggle Actuation	Horizontal
Configuration Features	
Configuration (Pole-Throw)	Four Pole - Double Throw
Operating Function	On None On
Electrical Characteristics	
Dielectric Strength	1000 VAC
UL/CSA Current Rating (125V)	3 A
Insulation Resistance	1000 MΩ
Toggle Switch Voltage Rating	20 VDC
Body Features	
Toggle Switch Seal Type	Terminal Seal (Epoxy)
Bushing Style	Unthreaded
Contact Features	
Contact Base Material	Gold

TT41NGRA1

Toggle Switches, Four Pole - Double Throw Configuration (Pole-Throw), Sealed, Gold, Gold, Terminal Seal (Epoxy), Baton Short, On None On, .4 A, 20 VDC



Switch Contact Plating Material	Gold
Toggle Switch Contact Current Rating	.4 A
Termination Features	
Termination Type	Right Angle
Mechanical Attachment	
Toggle Switch Mounting Type	Through Hole
Housing Features	
Process Sealed	No
Dimensions	
Toggle Length	5.61 mm[.221 in]
Industry Standards	
UL Flammability Rating	UL 94V-0
Other	
Comment	Each switch is provided with a disposable boot used only during cleaning operation.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2018 (181) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

TT41NGRA1

Toggle Switches, Four Pole - Double Throw Configuration (Pole-Throw), Sealed, Gold, Gold, Terminal Seal (Epoxy), Baton Short, On None On, .4 A, 20 VDC



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





TE Part # 5-1437561-0 TT11DGWW2T=SW TOGGLE WITH WIRE



TE Part # 1-1437562-6 TT21NGRA1ES=SP TOGGLE SEALED



TE Part # 6-1437562-1 TT23P8T1/4=DP LOCKING TOGGLE S



TE Part # 9-1437562-5 TTE13D8T1/4=SW TOGGLE WATERTIG

Customers Also Bought



TT41NGRA1

Toggle Switches, Four Pole - Double Throw Configuration (Pole-Throw), Sealed, Gold, Gold, Terminal Seal (Epoxy), Baton Short, On None On, .4 A, 20 VDC





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-1437562-9_A_c-6-1437562-9-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-1437562-9_A_c-6-1437562-9-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-1437562-9_A_c-6-1437562-9-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages SWITCHES_CORE_PROGRAM_CATALOG

English