


# LQ-4A-30



Item number 64.1039-\*

Stackable, Ø 4 mm, with spring-loaded MULTILAM for self-assembly of test leads. Solder connection.

Technical data	
Diameter of plug system	4 mm
Rated Values	30 V, 19 A / 60 V, 19 A
Surface treatment electrical contact	Au
Base material electrical contact	CuZn
Standard color(s) *	<span style="background-color: yellow; border: 1px solid black; padding: 2px;">20</span> <span style="background-color: black; color: white; border: 1px solid black; padding: 2px;">21</span> <span style="background-color: red; color: white; border: 1px solid black; padding: 2px;">22</span> <span style="background-color: blue; color: white; border: 1px solid black; padding: 2px;">23</span> <span style="background-color: cyan; color: white; border: 1px solid black; padding: 2px;">24</span> <span style="background-color: green; color: white; border: 1px solid black; padding: 2px;">25</span> <span style="background-color: purple; color: white; border: 1px solid black; padding: 2px;">26</span> <span style="background-color: orange; color: white; border: 1px solid black; padding: 2px;">27</span> <span style="background-color: grey; color: white; border: 1px solid black; padding: 2px;">28</span> <span style="border: 1px solid black; padding: 2px;">29</span>
Outer diameter	3.0 mm
Test accessory acc. to	IEC EN 61010-031
Component parts	KT-L-4-30