

Product type designation

Product description

IE FC RJ45 Plug 180 (4x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 180 4x 2, RJ45 plug-in connector; CAT6A; (10/100/1000/10000 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC Cable 4x 2 (AWG24); 180° cable outlet 1 pack = 10 units



Suitability for use

For connection to IE FC TP cables 4x2, suitable for fast assembly with the FastConnect system

Transmission rate

Transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s

Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

8

1

Type of electrical connection

- for network components or terminal equipment

RJ45 connector

Type of electrical connection / FastConnect

Yes

Mechanical data

Material / of the enclosure

metal

Number of reuses

10

Locking mechanism design

other

Design, dimensions and weight

Type of cable outlet	180° cable outlet
Width	13.7 mm
Height	16 mm
Depth	55 mm
Net weight	35 g
Connectable cable cross-section	8 ... 8 mm

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Product properties, functions, components / general	
Product feature	
<ul style="list-style-type: none"> PoE capability 	Yes
<ul style="list-style-type: none"> PoE+capability 	Yes
<ul style="list-style-type: none"> silicon-free 	Yes
Product component	
<ul style="list-style-type: none"> strain relief 	Yes

Standards, specifications, approvals	
Certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
<ul style="list-style-type: none"> UL approval 	Yes
<ul style="list-style-type: none"> cULus approval 	Yes
<ul style="list-style-type: none"> Railway application in accordance with EN 50155 	No
Standard for structured cabling	Cat6A

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	01/10/2019