SIEMENS

Data sheet

Product description

6GK5104-0BA00-1SA2

Test access port with two network ports and two diagnostic ports for discharging telegrams from the network ports (both transmission directions)

SCALANCE TAP104 Text access port to telegram cable, 2 x RJ45 ports, 10/100MBit/s, LED diagnostics, 24 V DC Supply voltage, Manual



Product type designation	SCALANCE TAP104
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
 for network components or terminal equipment 	2; RJ45 with securing collar
Interfaces / others	
Number of electrical connections	
• for power supply	1
Type of electrical connection	
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V

• external / minimum	18 V
	31.2 V
external / maximum	
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.5 A / 60 V
Consumed current / maximum	0.06 A
Power loss [W]	4.44.101
• at DC / at 24 V	1.44 W
Permitted ambient conditions	
Ambient temperature	
 during operation 	-40 +70 °C
• during storage	-40 +85 °C
• during transport	-40 +85 °C
Relative humidity	
 at 25 °C / without condensation / during 	95 %
operation / maximum	
Protection class IP	IP20
Design, dimensions and weight	
Design	compact
Width	35 mm
Height	152 mm
Depth	135 mm
Net weight	0.24 kg
Mounting type	Installation with a stand and in 19" rack using accessory
	components
• 35 mm DIN rail mounting	Yes
 wall mounting 	Yes
 S7-300 rail mounting 	Yes
 S7-1500 rail mounting 	Yes
Product functions / Redundancy	
Product function	
 Parallel Redundancy Protocol (PRP)/operation 	Yes
in the PRP-network	
 Parallel Redundancy Protocol 	No
(PRP)/Redundant Network Access (RNA)	
Standards, specifications, approvals	
Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
 for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
• for emitted interference	EN 61000-6-4 (Class B)

• for interference immunity

EN 61000-6-2

Standards, specifications, approvals / CE	
Certificate of suitability / CE marking	Yes
Standards, specifications, approvals / miscellaneou	IS
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	No
 KC approval 	Yes
Further Information / Internet Links	
Internet-Link	
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
 to website: Industrial communication 	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx Download Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third- party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	11/27/2018