6GK5116-0BA00-2AB2

Data sheet



SCALANCE XB116 unmanaged IE switch, 16x 10/100 Mbit/s RJ45 ports; for setting up small star and line topologies; LED diagnostics, IP20, redundant power supply, 24 V AC/DC manual available as a download .

product type designation	SCALANCE XB116
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	16; RJ45
interfaces / other	
number of electrical connections	
for power supply	1
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	4.8 W
supply voltage / 1 / rated value	19.2 28.8 V
consumed current / 1 / maximum	0.2 A
 product component / 1 / fusing at power supply input 	Yes
fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V
type of voltage / 2 / of the supply voltage	
supply voltage / 2 / rated value	19.2 28.8 V
ambient conditions	
ambient temperature	
during operation	0 60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	80 mm
height	117 mm
depth	109 mm
net weight	0.375 kg
fastening method	
 35 mm top hat DIN rail mounting 	Yes
wall mounting	No

a C7 200 rail mounting	No
• S7-300 rail mounting	No
S7-1500 rail mounting	No
product functions / management, configuration, engineeri	ng
product function	A.
multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
product function / switch-managed	No
product functions / redundancy	
product function	
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
Parallel Redundancy Protocol (PRP)/Redundant	No
Network Access (RNA)	
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP.
	IIC, T4
for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
 for emitted interference 	EN 61000-6-4 (Class B)
• for interference immunity	61000-6-2
MTBF	80 y
reference code	Ve
according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environn	
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability	on the horizontal and the horizo
• IECEx	Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA IIC T4
<u></u>	Gc
 CCC / for hazardous zone according to GB standard 	Yes
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
 KC approval 	Yes
 Regulatory Compliance Mark (RCM) 	Yes
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security
	functions that support the secure operation of plants, solutions,
	machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens'
	products and solutions undergo continuous development. Siemens
	recommends strongly that you regularly check for product updates. For
	the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and
	integrate each component into a holistic, state-of-the-art industrial
	security concept. Third-party products that may be in use should also be
	considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about
	product updates as they occur, sign up for a product-specific newsletter.
	For more information, visit http://support.automation.siemens.com.
last modified:	(V3.4) 2/8/2022 ©