Data sheet



SCALANCE SC646-2C Cyber Security Appliance; for protection of devices and networks in discrete manufacturing and the process industry for protection of industrial communication with firewall and VPN; Further functions: address translation (NAT/NAPT); connection to SINEMA RC; 4x port electrical 10/100/1000 Mbit/s RJ45 and 2x combo port electrical or optical; 10/100/1000 Mbit/s RJ45 or 100 Mbit/s SFP or 1000 Mbit/s

Transfer rate		
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s	
Interfaces		
Number of electrical/optical connections / for network	6	
components or terminal equipment / maximum		
Number of electrical connections		
 for signaling contact 	1	
for power supply	1	
for redundant voltage supply	1	
Type of electrical connection		
 for signaling contact 	2-pole terminal block	
• for power supply	4-pole terminal block	
design of the removable storage / C-PLUG	Yes	
Signal inputs/outputs		
Number of electrical connections		
 for digital input signals 	1	
Type of electrical connection		
 for digital input signals 	2-pole terminal block	

Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Supply voltage / external	24 V
Supply voltage / external	9.3 31.2 V
Type of voltage / of the supply voltage	DC
Consumed current / maximum	0.4 A
Power loss [W]	
• at DC / at 24 V / typical	9.6 W
• Note	(with plugged-in SFPs)
Ambient conditions	
Ambient temperature	
during operation	-40 +70 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
Relative humidity / at 25 °C / without condensation /	95 %
during operation / maximum	
Protection class IP	IP20
Design, dimensions and weights	
Design	compact
Width	60 mm
Height	145 mm
Depth	125 mm
Net weight	0.58 kg
Mounting type	Fixing bolt with additional screw protection
Mounting type	
• 35 mm DIN rail mounting	Yes
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
wall mounting	Yes
Product features, product functions, product compo	nents / general
Product function / DynDNS client	Yes
Product functions / management, configuration, eng	gineering
Product function	
• CLI	Yes
 web-based management 	Yes
MIB support	Yes
Protocol / is supported	
• HTTP	No
• HTTP	No

• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
Type of configuration	WBM, CLI, SNMP

Product functions / Diagnostics		
Product function		
SysLog	Yes	
Packet Filter Log	Yes	
Audit Log	Yes	
System log	Yes	

Product functions / DHCP		
	Product function	
	DHCP client	Yes
	DHCP server - internal network	Yes

Product functions / Routing	
Product function / Static IP routing	Yes
Product functions / Security	
Firewall version	stateful inspection

•	
Firewall version	stateful inspection
Product function / with VPN connection	IPsec, OpenVPN (as client for SINEMA RC)
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1, SHA-256, SHA-384, SHA-512
Number of possible connections / with VPN connection	200
Product function	
 Password protection 	Yes
Bandwidth limiting	No
• NAT/NAPT	Yes

Product functions / redundancy	
Product function	
 Ring redundancy 	Yes
 High Speed Redundancy Protocol (HRP) 	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Product functions / time	
Protocol / is supported / NTP	Yes
Product feature / Hardware real-time clock w. battery	Yes
backup	

Standards, specifications, approvals

Standard	
• for FM	FM 3611 (available soon)
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
• for safety / from CSA and UL	UL 60950 / CSA C22.2 No. 60950-1-03, CSA C22.2 No. 213- M1987 (in preparation)
• for emitted interference	EN 61000-6-4: 2007
• for interference immunity	EN 61000-6-2: 2005
Certificate of suitability	AS/NZS 2064 (Class A), EN 61000-6-2, EN 61000-6-4
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	Yes
Bureau Veritas (BV)	Yes
DNV GL	Yes
ONV OL	

Yes

Product extension /	optional / C-PLUG

Internet	Link

• to website: Selector SIMATIC NET

SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

 $\underline{\text{https://support.industry.siemens.com}}$

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

02/05/2020