SIEMENS

Data sheet

6GK5722-1FC00-0AA0

Product type designation



SCALANCE W722-1 RJ45

IWLAN client, SCALANCE W722-1, RJ45, 1 radio, 1 R-SMA antenna port, iFeatures support IEEE 802.11a/b/g/h/n, 2.4/5 GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, terminal block, IP20, 0... +55°C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x terminal block; for operation outside of USA/Israel

Transmission rate	
Transfer rate	
with WLAN / maximum	150 Mbit/s
• for Industrial Ethernet	10, 100 Mbit/s
Transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
• maximum	100 Mbit/s

Interfaces	
Number of electrical connections	
 for network components or terminal equipment 	1
• for power supply	1
 for redundant voltage supply 	0
Type of electrical connection	
 for network components or terminal equipment 	RJ45 socket
• for power supply	3-pole screw terminal
design of the removable storage	
• C-PLUG	No

• KEY-PLUG	No
Interfaces / wireless	
Number of radio cards / permanently installed	1
Number of electrical connections / for external	1
antenna(s)	
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted	Yes
directly on device	
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1	
• from terminal block	19.2 V
Supply voltage / 2	
• from terminal block	28.8 V
Consumed current	
• at DC / at 24 V / typical	0.15 A
Power loss [W]	
• at DC / at 24 V / typical	3.6 W
Permitted ambient conditions	
Ambient temperature	
during operation	0 55 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
Relative humidity / at 25 °C / without condensation /	95 %
during operation / maximum	
Ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE
	W761-1 RJ45 or W72x-1 RJ45 product must be installed in an
	enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
Protection class IP	IP20
Design, dimensions and weight	
Width	50 mm
Height	114 mm
Depth Width / of the englacure / without entenne	74 mm
Width / of the enclosure / without antenna	50 mm
Height / of the enclosure / without antenna	114 mm
Depth / of the enclosure / without antenna	74 mm
Net weight	0.13 kg
Mounting type	No
• S7-300 rail mounting	No No
S7-1500 rail mounting	No

• 35 mm DIN rail mounting

Yes

• wall mounting No

Wireless frequencies

Operating frequency

• for WLAN in 2.4 GHz frequency band 2.41 ... 2.48 GHz

• for WLAN in 5 GHz frequency band

4.9 ... 5.8 GHz

Product properties, functions, components / general	
Product function / Access Point Mode	No
Product function / Client Mode	Yes
Product function	
• iPCF client	Yes
• iPCF-MC client	Yes
Number of iPCF-capable radio modules	1
Product function / iPRP	Yes

Product functions / management, configuration	
Number of manageable IP addresses / in client	4
Product function	
• CLI	Yes
web-based management	Yes
MIB support	Yes
• TRAPs via email	Yes
 Configuration with STEP 7 	Yes
 configuration with STEP 7 in the TIA Portal 	Yes
• WDS	No
Protocol / is supported	
 Address Resolution Protocol (ARP) 	Yes
• ICMP	Yes
● Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	No
Identification & maintenance function	
 I&M0 - device-specific information 	Yes
 I&M1 – higher-level designation/location designation 	Yes

Product functions / Diagnosis

Product function

• PROFINET IO diagnosis

• Link Check

Yes No

	N
 connection monitoring IP-Alive 	No
SysLog	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
Product functions / VLAN	
Product function	
 function VLAN with IWLAN 	No
Product functions / DHCP	
Product function	
DHCP client	Yes
in Client Mode / DHCP server via LAN	Yes
DHCP Option 82	Yes
Product functions / Redundancy	
Protocol / is supported	
• STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
Product functions / Security	
Product function	
 ACL - MAC-based 	Yes
 Management security, ACL-IP based 	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	Yes
 access protection according to IEEE802.11i 	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported	
• SSH	Yes
• RADIUS	Yes
Product functions / Time	
Protocol / is supported	
• NTP	Yes
• SNTP	Yes
• SIMATIC Time	Yes
Standards, specifications, approvals	
Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4

• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
Certificate of suitability	
 EC declaration of conformity 	Yes
• CE marking	Yes
• C-Tick	Yes
● E1 approval	No
 Railway application in accordance with EN 50155 	No
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
 Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	No
 Power-over-Ethernet according to IEEE802.3at for type 2 	No
Standard for wireless communication	
● IEEE 802.11a	Yes
● IEEE 802.11b	Yes
● IEEE 802.11e	Yes
● IEEE 802.11g	Yes
● IEEE 802.11h	Yes
● IEEE 802.11i	Yes
● IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at:
	www.siemens.de/funkzulassungen
Marine classification association	Na
 American Bureau of Shipping Europe Ltd. (ABS) 	No
Bureau Veritas (BV)	No
• DNV GL	No
Lloyds Register of Shipping (LRS)	No
Nippon Kaiji Kyokai (NK)	No
Polski Rejestr Statkow (PRS)	No
 Royal Institution of Naval Architects (RINA) 	No
Accessories	
accessories	24 V DC screw terminal included in scope of delivery
Further Information / Internet Links	
Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool

to the website: IWLANto website: Industry Mall

• to website: Information and Download Center

• to website: Image database

to website: CAx Download Managerto website: Industry Online Support

http://www.siemens.com/iwlan

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

10/30/2018