

product type designation

Antenna ANT 8

SIMATIC RF200/RF300 antenna ANT 8 M8x 38 mm, IP67, -25 to +70 °C, without connection cable.



suitability for operation

RF250R / RF350M

radio frequencies

transmission frequency / rated value

13.56 MHz

electrical data

type of electrical connection / of the antenna

M8, 4-pin

design of plug-in connection

female

mechanical data

material

Stainless steel V2A

color

Silver

tightening torque / of the screw for securing the equipment / maximum

3 N·m

mounting distance

- relating to metal surfaces / recommended / minimum

0 m

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-25 ... +70 °C

-40 ... +85 °C

-40 ... +85 °C

protection class IP

IP67, front

shock resistance

according to EN 60721-3-7 Class 7M2

shock acceleration

500 m/s²

vibrational acceleration

200 m/s²

design, dimensions and weights

depth

38 mm

diameter

8 mm

net weight

10 g

fastening method

2 stainless steel cscrew nuts M8 x 1.0 (included)

standards, specifications, approvals

certificate of suitability

CE, FCC, IC, cULus

certificate of suitability

- IECEx

No

reference code

- according to IEC 81346-2
- according to IEC 81346-2:2019

TF

TFB

accessories

accessories

Antenna cable

further information / internet-Links

Internet-Link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

11/3/2021 