

Product type designation

MDS D526 transponder

Transponder MDS D526 only for RF200/RF300 Gen2, disk ISO 15693, chip type FUJITSU MB89R112, 8192-byte FRAM user memory 50 x 3.2 mm (DxH); Minimum order quantity 50 units



Wireless frequencies	
Operating frequency / Rated value	13.56 MHz
Range / maximum	400 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	ISO 15693
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product feature / multitag-capable	Yes
Electrical data	
Product component / Backup battery	No
Memory	
Type of memory	FRAM
Storage capacity / of the user memory	8192 byte
Type of memory organization	UID (fixed code) 8 bytes, user memory 8192 bytes, configuration memory 40 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	1000000000000

Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the user memory
Type of transponder chip used	Fujitsu MB89R112

Mechanical data

Material	PA6.6 GF
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	25 mm

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during read/write access 	-25 ... +85 °C
<ul style="list-style-type: none"> outside the read/write area 	-40 ... +100 °C
<ul style="list-style-type: none"> during storage 	-40 ... +100 °C
Protection class IP	IP68
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight

Height	3.6 mm
Diameter	50 mm
Net weight	13 g
Mounting type	M4 screw

Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> printable 	No

Standards, specifications, approvals

MTBF	228 y
------	-------

Accessories

accessories	Mounting support and spacer
-------------	-----------------------------

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/ident/rfid
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

01/09/2019