


Item no.: 733-336
 Product description: Male header (for PCBs) Straight solder pin 0.8 x 0.8 mm 6-pole
 Pin spacing 2.5 mm / 0.098 in 100% protected against
 mismatching Vertical PCB mounting with closed end



Produkt kann von Bild abweichen / product may differ

Packing unit 200 pieces

RoHS compliant

| | |
|----------------------------|----------------|
| Weight | 0.883 g |
| Color | light grey |
| pole count | 6 |
| Height | 8.9 mm |
| Height | 0.35 in |
| Width | 17.5 mm |
| Width | 0.689 in |
| Depth | 7.8 mm |
| Depth | 0.307 in |
| Pin spacing from | 2.5 mm |
| Pin spacing from | 0.098 in |
| Rating based on | IEC/EN 60664-1 |
| Overvoltage category EN I | III |
| Pollution degree | 2 |
| Measured voltage EN | 160 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 6 A |
| Overvoltage category EN II | II |

| | |
|------------------------|--------|
| Pollution degree | 2 |
| Measured voltage EN | 320 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 6 A |



| | |
|---|---------------------------|
| Overvoltage category EN III | III |
| Degree of pollution | 3 |
| Rated voltage EN | 80 V |
| Rated surge voltage | 2.5 kV |
| Nominal current | 6 A |
| Solder pin length [mm] | 4.6 mm |
| Solder pin width A [mm] | 0.8 mm |
| Solder pin width B [mm] | 0.8 mm |
| Diameter of drilled hole [mm] | 1.1 mm |
| Tolerance of drilled hole diameter [mm] | 0.1 mm |
| Material group | I |
| Insulating material | PA 6.6 |
| Temperature stability | -60 °C to +100 °C |
| Flammability category, based on UL 94 | V0 |
| Contact material | Electrolytic copper (Ecu) |
| Contact plating | tin-plated |



| Item number | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-------------|------------------|-------------------|-------------|-------------|-----------------------------------|
| 733-336 | ABS | 04-HG469925/1-PDA | 250 | 4 | |
| 733-336 | BV | 11915/A0 | 250 | 4 | |
| 733-336 | CCA | NL5640 | 250 | 4 | |
| 733-336 | CSA | 154112-1465035 | 150 | 4 | 28-20 |
| 733-336 | DNV | E-9218 | 250 | 4 | |
| 733-336 | GL | 17296-00HH | 250 | 4 | |
| 733-336 | KEMA | 2077592.01 | 250 | 4 | |
| 733-336 | LR | 96/20035 | 250 | 6 | |
| 733-336 | RMR | 11130002 | 250 | 4 | |
| 733-336 | UR | E45171 | 250 | 4 | |
| 733-336 | UR | E45172 | 150 | 4 | 28-20 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected