

# Field Side Connection Module

0 V DC








Fig. 750 Series/Technical data see page 24/Delivered without miniature WSB markers  
750/753 Series marking see pages 10 ... 11 / 12 ... 13

The field side connection module provides 0 V potential for the outputs of the 8-channel output module 750-530.

This eliminates the need for additional terminal blocks.

The 24V supply and 0V potential are derived from the internal power jumper contacts of an adjacent upstream I/O module. A connection of the potentials to the downstream I/O modules is made automatically via the power jumper contacts when snapping the I/O modules together. The 24V power is provided to all eight (8) field side CAGE CLAMP® connections and the 0V potential passed through without being used by the module.

Description	Item No.	Pack. Unit
Field Side Connection	750-604	1
Field Side Connection (without connector)	753-604	1
Accessories	Item No.	Pack. Unit
 753 Series Connectors	753-110	25
 Coding elements	753-150	100
Miniature WSB Quick marking system		
 plain	248-501	5
 with marking	see pages 352 ... 353	
Approvals	Also see "Approvals Overview" in Section 1	
Conformity marking	CE	
Shipbuilding	ABS, DNV, GL, KR	
UL 508	Class I, Div. 2, Grp. ABCD, T4	
ANSI/ISA 12.12.01	I M2 / II 3 GD Ex nA IIC T4	
EN 60079-0, -15 EN 61241-0, -1		

Technical Data	
Voltage via power jumper contacts (max.)	24 V DC (-25 % ... + 30 %)
Current via power jumper contacts (max.)	10 A DC
Wire connection	CAGE CLAMP®
Cross sections	0.08 mm² ... 2.5 mm² / AWG 28 ... 14
Stripped lengths, 750/753 Series	8 ... 9 mm / 0.33 in
	9 ... 10 mm / 0.37 in
Width	12 mm
Weight	48.5 g
EMC: CE - immunity to interference	acc. to EN 61000-6-2 (2005)
EMC: CE - emission of interference	acc. to EN 61000-6-4 (2007)
EMC: marine applications	
- immunity to interference	acc. to Germanischer Lloyd (2003)
EMC: marine applications	
- emission of interference	acc. to Germanischer Lloyd (2003)