

1.5 ... 4 mm<sup>2</sup> "s"

400 V/4 kV/2

I<sub>N</sub> 32 A

 12 mm / 0.47 in.



Item No.	Pack. Unit
<b>PUSH WIRE®</b> connector for junction boxes and solid conductors up to 4 mm <sup>2</sup> , 2-conductor connector, transparent brown housing, white cover	
<b>773-602</b>	100

<b>Description</b>	PUSH WIRE® connector for junction boxes; 2-conductor terminal block; transparent housing; yellow cover		
<b>Remarks</b>	<b>Safety information 2:</b> When using conductors of exclusively the same cross section, 0.75 mm <sup>2</sup> /AWG 18 is also possible.		
<b>Item properties</b>	<b>Miscellaneous</b>		
	<b>Name</b>	<b>Value</b>	<b>Unit</b>
	Total number of connection points	2	
	Total number of potentials	1	
	Pollution degree (1)	2	
	Rated voltage (II / 2) [V]	400	V
	Rated impulse voltage (II / 2) [kV]	4	kV
	Rated current [A]	24	A
	Connection technology	Push-in CAGE CLAMP®	
	Number of connection points connector	2	
	Actuation type	Push-in	
	Connectable conductor materials	Copper	
	Solid conductor	0.75 ... 2.5 mm <sup>2</sup> / 18 ... 12 AWG	
	Stranded conductor	1.5 ... 2.5 mm <sup>2</sup> / 16 ... 12 AWG	
	Strip length	12 mm / 0.47 Inch	
	Type of wiring	Side-entry wiring	
	Fire load [MJ]	0.037	MJ
	Weight [g]	1.538	g
	Width	9.2 mm / 0.362 Inch	
	Height	13.1 mm / 0.516 Inch	
	Depth	19.5 mm / 0.768 Inch	
	Safety information 1	In grounded power lines	