

1.5 ... 4 mm² "s"

400 V/4 kV/2

I_N 32 A

 12 mm / 0.47 in.



Color	Item No.	Pack. Unit
PUSH WIRE® connector for junction boxes and solid conductors up to 4 mm ² ,		
4-conductor connector,		
transparent brown housing, red cover		
	773-604	100

Description	PUSH WIRE® connector for junction boxes; 4-conductor terminal block; transparent housing; orange cover
Remarks	Safety information 2: When using conductors of exclusively the same cross section, 0.75 mm ² /AWG 18 is also possible.

Item properties	Miscellaneous		
	Name	Value	Unit
	Total number of connection points	4	
	Total number of potentials	1	
	Pollution degree (1)	2	
	Rated voltage (II / 2) [V]	400	V
	Rated impulse voltage (II / 2) [kV]	4	kV
	Connection technology	Push-in CAGE CLAMP®	
	Number of connection points connector	4	
	Actuation type	Push-in	
	Connectable conductor materials	Copper	
	Solid conductor	0.75 ... 2.5 mm ² / 18 ... 12 AWG	
	Stranded conductor	1.5 ... 2.5 mm ² / 16 ... 12 AWG	
	Strip length	12 mm / 0.47 Inch	
	Type of wiring	Side-entry wiring	
	Fire load [MJ]	0.056	MJ
	Weight [g]	2.511	g
	Width	13 mm / 0.512 Inch	
	Height	13.1 mm / 0.516 Inch	
	Depth	19.5 mm / 0.768 Inch	
Safety information 1	In grounded power lines		