



DESIGN KIT

WE-PDA SMD Power Inductor



SIZE:

7332 / 7345

TECHNICAL DATA:

L: 1.0 – 1000 μ H
 I_R : 0.23 – 3.7 A
 I_{sat} : 0.25 – 8.0 A
 R_{DC} : 36.0 – 7200 m Ω

Order Code 784 778

Version 1.0

WE-PDA SMD Power Inductor



7345	784 777 010	L: 1.0 μ H I_R : 3.70 A I_{sat} : 8.0 A R_{DC} : 38.5 m Ω	784 777 022	L: 2.2 μ H I_R : 2.70 A I_{sat} : 5.25 A R_{DC} : 61.0 m Ω	784 777 033	L: 3.3 μ H I_R : 2.50 A I_{sat} : 4.70 A R_{DC} : 70.0 m Ω	784 777 047	L: 4.7 μ H I_R : 2.35 A I_{sat} : 3.70 A R_{DC} : 84.0 m Ω	784 777 068	L: 6.8 μ H I_R : 2.20 A I_{sat} : 3.20 A R_{DC} : 98.0 m Ω	784 777 082	L: 8.2 μ H I_R : 2.00 A I_{sat} : 2.80 A R_{DC} : 117 m Ω	784 777 100	L: 10.0 μ H I_R : 1.90 A I_{sat} : 2.60 A R_{DC} : 126 m Ω	
	784 777 220	L: 22.0 μ H I_R : 1.40 A I_{sat} : 1.80 A R_{DC} : 215 m Ω	784 777 470	L: 47.0 μ H I_R : 1.15 A I_{sat} : 1.25 A R_{DC} : 300 m Ω	784 777 101	L: 100 μ H I_R : 0.72 A I_{sat} : 0.80 A R_{DC} : 470 m Ω	784 777 221	L: 220 μ H I_R : 0.50 A I_{sat} : 0.55 A R_{DC} : 1135 m Ω	784 777 471	L: 470 μ H I_R : 0.35 A I_{sat} : 0.38 A R_{DC} : 2720 m Ω	784 777 102	L: 1000 μ H I_R : 0.25 A I_{sat} : 0.28 A R_{DC} : 5750 m Ω			
	7332	784 778 010	L: 1.0 μ H I_R : 3.50 A I_{sat} : 7.0 A R_{DC} : 36.0 m Ω	784 778 022	L: 2.2 μ H I_R : 3.10 A I_{sat} : 5.00 A R_{DC} : 50.0 m Ω	784 778 033	L: 3.3 μ H I_R : 2.65 A I_{sat} : 3.70 A R_{DC} : 65.0 m Ω	784 778 047	L: 4.7 μ H I_R : 2.40 A I_{sat} : 3.10 A R_{DC} : 79.0 m Ω	784 778 068	L: 6.8 μ H I_R : 2.30 A I_{sat} : 2.50 A R_{DC} : 94 m Ω	784 778 082	L: 8.2 μ H I_R : 2.20 A I_{sat} : 2.40 A R_{DC} : 103 m Ω	784 778 100	L: 10.0 μ H I_R : 1.85 A I_{sat} : 2.20 A R_{DC} : 126 m Ω
		784 778 220	L: 22.0 μ H I_R : 1.55 A I_{sat} : 1.60 A R_{DC} : 187 m Ω	784 778 470	L: 47.0 μ H I_R : 1.10 A I_{sat} : 1.05 A R_{DC} : 348 m Ω	784 778 101	L: 100 μ H I_R : 0.72 A I_{sat} : 0.75 A R_{DC} : 720 m Ω	784 778 221	L: 220 μ H I_R : 0.48 A I_{sat} : 0.50 A R_{DC} : 1620 m Ω	784 778 471	L: 470 μ H I_R : 0.30 A I_{sat} : 0.35 A R_{DC} : 3300 m Ω	784 778 102	L: 1000 μ H I_R : 0.23 A I_{sat} : 0.25 A R_{DC} : 7200 m Ω		

EMC COMPONENTS | **INDUCTORS** | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | LEDs | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | POWER ELEMENTS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2014

www.we-online.com

All products
in stock!