


	Sockets for miniature switching relay and optocoupler	
--	---	--



Description	Item No.	Pack. Unit
JUMPFLEX® socket for miniature switching relay and optocoupler, 24 V AC/DC for DIN 35 rail	857-104	1
JUMPFLEX® socket for miniature switching relay and optocoupler, 110 V AC/DC for DIN 35 rail	857-107	1
JUMPFLEX® socket for miniature switching relay and optocoupler, 230 V AC/DC for DIN 35 rail	857-108	1

Technical Data		Accessories see page 52 + 62 ... 63
Status indication	LED yellow	
Operating temperature	-25 °C ... +60 °C	
Storage temperature	-40 °C ... +70 °C	
Dimensions (mm) W x H x L	6 x 81 x 94	
Wire connection	Height from upper-edge of DIN 35 rail CAGE CLAMP®S	
Cross sections	0.34 mm ² ... 2.5 mm ² / AWG 22 ... 14	
Stripped lengths	9 ... 10 mm / 0.37 in	

Assignment Socket / Replacement Relay / Replacement Optocoupler				
	Input Voltage	Item No.	Socket	Replacement Relays or Optocouplers
Miniature Switching Relays	12 V DC	857-303	857-103	857-150
	24 V DC	857-304	857-104	857-152
	48 V DC	857-305	857-105	857-154
	60 V DC	857-306	857-106	857-155
	110 V DC	857-307	857-107	857-155
	220 V DC	857-308	857-108	857-155
	24 V AC/DC	857-354	857-104	857-152
	115 V AC/DC	857-357	857-107	857-155
	230 V AC/DC	857-358	857-108	857-155
	Miniature Switching Relays (gold contacts)	24 V DC	857-314	857-104
110 V DC		857-317	857-107	857-157
220 V DC		857-318	857-108	857-157
24 V AC/DC		857-364	857-104	857-153
115 V AC/DC		857-367	857-107	857-157
230 V AC/DC		857-368	857-108	857-157
24 V DC		857-704	857-104	857-164
115 V AC/DC		857-707	857-107	857-165
230 V AC/DC		857-708	857-108	857-165
24 V DC		857-714	857-104	857-167
Solid State Relays	115 V AC/DC	857-717	857-107	857-168
	230 V AC/DC	857-718	857-108	857-168
	24 V DC	857-724	857-104	857-161
	115 V AC/DC	857-727	857-107	857-162
	230 V AC/DC	857-728	857-108	857-162