

**Industrial Ethernet
IE-XM-RJ45/IDC-IP67**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com



SnapIn plug-in connectors according to IEC 61076-3-106
ver.6 in plastic, with RJ45 insert

General ordering data

Type	IE-XM-RJ45/IDC-IP67
Order No.	8808440000
Version	Mounting flange, RJ45 module flange, straight, Cat.6 (ISO/IEC 11801), IP67
GTIN (EAN)	4032248506026
Qty.	1 pc(s).

Industrial Ethernet IE-XM-RJ45/IDC-IP67

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Technical data

Dimensions and weights

Net weight 54.7 g

Temperatures

Operating temperature -40 °C...70 °C Storage temperature
Installation temperature

General data

Connection 1	RJ45	Connection 2	IDC
Description of article		Configuration	Installation flange with mounting frame and RJ45 module with IDC connection captive lid
Wiring	RJ45 module flange, straight Colour-coded pin assignment according to EIA/TIA T568 A., EIA/TIA T568 B	Colour	Light Grey
Housing main material	PA 66, UL 94: V-0	Category	Cat.6 (ISO/IEC 11801)
Contact surface	Gold over nickel	Type of mounting	Cabinet, Distribution box
Shielding	360° shield contact	Protection degree	IP67
Plugging cycles	750		

Standards

Connector standard IEC 61076-3-106 Var. 6, IEC 60603-7-5 Certificate No. (GERMLLOYD) 33451-06

Downloads

GL Approval Guidelines GL_Certificate.pdf GOST Approval POCC DE.ME25.B01411.pdf

Classifications

ETIM 3.0	EC001264	ETIM 4.0	EC001264
ETIM 5.0	EC001264	ETIM 6.0	EC001121
UNSPSC	43-17-27-10	eClass 5.1	27-25-05-04
eClass 6.2	27-25-05-04	eClass 7.1	27-25-05-04
eClass 8.1	19-17-01-25	eClass 9.0	19-17-01-25
eClass 9.1	27-44-09-90		

Approvals

Approvals



ROHS Conform

Data sheet**Industrial Ethernet
IE-XM-RJ45/IDC-IP67**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings**Dimensioned drawing**