

INSTA
CP SNT 48W 48V 1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .
 The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.
 They are available with output voltages from 5 V to 48 V.

General ordering data

Type	CP SNT 48W 48V 1A
Order No.	8879230000
Version	Power supply, switch-mode power supply unit, 48 V
GTIN (EAN)	4032248615148
Qty.	1 pc(s).

**INSTA
CP SNT 48W 48V 1A**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	70 mm	Width (inches)	2.756 inch
Height	90.5 mm	Height (inches)	3.563 inch
Depth	62.5 mm	Depth (inches)	2.461 inch
Weight	0.2 kg	Net weight	333 g

Temperatures

Humidity at operating temperature	5...95% (indoor), $T_u = 40^\circ\text{C}$, no condensation	Operating temperature	-10 °C...70 °C (Derating ab 55 °C)
Storage temperature	-20 °C...85 °C		

Input

Connection system	Screw connection	DC input voltage range	80...370 V DC
Input current	500 mA at rated load @ 230 V AC	Input current at 115 Vac	500 mA
Input current at 230 Vac	500 mA	Input frequency	50/ 60 Hz
Input fuse	Fusible link 2.5 A (T) / 250 V	Input voltage (voltage mode input)	85...264 V AC / 110...370 V DC
Overload current protection	Yes	Wire connection method	Screw connection

output

Control at 10...100% load	1%	Mains failure bridge-over time	11 ms @ 115 V AC / 50 ms @ 230 V AC
Max. capacitance at output	10000 μF	Max. residual ripple	120 mV _{SS}
Output current	1 A	Output power	48 W
Output voltage	48 V	Output voltage	46...55 V (adjustable via potentiometer)
Output voltage type	DC	Overload protection	105 %...150 % I_{const} of max. output load; automatic reset
Parallel connection option	Max. 3 devices (rated voltages are to be calibrated at ± 20 mV)	Surge protection	Varistor
Wire connection method	Screw connection		

General data

Building Width	62.5 mm	Building height	90.5 mm
Degree of efficiency at max. load	80%	EMC standards	EN 55011, EN 55022, EN 61000-3-2,-3, EN 61000-6-2,-3,-4
Installation advice	For side-by-side mounting, clearance: above/below > 30 mm	MTBF	> 500,000 h acc. to IEC 1709 (SN29500)
Mounting position, installation notice	horizontally, on terminal rail TS 35	Operating temperature	-10 °C...70 °C (Derating ab 55 °C)
Protection degree	IP20	Short-circuit protection	Yes
Standards	DIN EN 50178 (PELV), DIN EN 60950 (SELV)	Status indication	Green LED
Weight	0.2 kg		

Data sheet

**INSTA
CP SNT 48W 48V 1A**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Insulation coordination

Humidity at operating temperature	5...95% (indoor), T _u = 40°C, no condensation	electrical isolation, I/O rail	4 kV
electrical isolation, input-earth	1.5 kV	electrical isolation, input-output	3 kV
electrical isolation, output-earth	0.5 kV		

Connection data (input)

Connection system	Screw connection
-------------------	------------------

Signalling

Status indication	Green LED
-------------------	-----------

Approvals

Institute (UL)		Certificate No. (UL)	E252191
Institute (cURus)		Certificate No. (cURus)	E255651

Rated data UL

Certificate No. (UL)	E252191
----------------------	---------

Classifications

ETIM 3.0	EC001039	ETIM 4.0	EC002541
ETIM 5.0	EC002541	ETIM 6.0	EC002540
UNSPSC	30-21-18-01	eClass 5.1	27-04-90-02
eClass 6.2	27-04-90-04	eClass 7.1	27-04-90-04
eClass 8.1	27-04-90-04	eClass 9.0	27-04-07-03
eClass 9.1	27-04-07-01		

Product information

Descriptive text ordering data	The internal varistor found in a switch-mode power supply does not replace the necessary surge protection in a system.
--------------------------------	--

Approvals

Approvals	
ROHS	Conform

Data sheet**INSTA
CP SNT 48W 48V 1A****Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com**Technical data****Downloads**

Approval/Certificate/Document of Conformity	DE_PA5200_160310_003.pdf
Engineering Data	EPLAN, WSCAD
User Documentation	Information zur Gewährleistung Operating Instructions

Data sheet

**INSTA
CP SNT 48W 48V 1A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings

Electric symbol

