Millenium 3 Essential

→ Essential range: powerful but cost effective

- Industrial temperature range (-20 °C → +55 °C)
- Analog inputs 0-10 VDC, Potentiometer (0-20 mA/Pt100 with converters)
- Display versions:
 - Green LCD with 4 lines of 18 characters and configurable backlighting
 - Selective parameter setting: you can choose the parameters that can be adjusted on the front panel
- Expandable versions: open to XN network communication extensions and digital I/O or analog extensions





CD12/XD10

CD20/XD26





CB12/XB10

CB20/XB26

Part numbers

Essential "compact" range						
Туре	Input	Output	Supply	Code		
CD12	8 digital (including 4 analog)	4 relays 8 A	24 V ==	88970041		
	8 digital (including 4 analog)	4 solid state 0.5 A (including 1 PWM)	24 V ===	88970042		
	8 digital (including 4 analog)	4 relays 8 A	12 V ===	88970045		
	8 digital (including 4 analog)	4 solid state 0.5 A (including 1 PWM)	12 V ===	88970865		
CD20	12 digital (including 6 analog)	8 relays 8 A	24 V ===	88970051		
	12 digital (including 6 analog)	8 solid state 0.5 A (including 4 PWM)	24 V ===	88970052		
	12 digital (including 6 analog)	8 relays 8 A	12 V ===	88970055		
CB12	8 digital (including 4 analog)	4 relays 8 A	24 V ===	88970021		
	8 digital (including 4 analog)	4 solid state 0.5 A (including 1 PWM)	12 V ===	88970840		
CB20	12 digital (including 6 analog)	8 relays 8 A	24 V ===	88970031		
	12 digital (including 6 analog)	8 solid state 0.5 A (including 4 PWM)	24 V == Obsolete	88970806		

Essential "expandable" range						
Туре	Input	Output	Supply	Code		
XD10	6 digital (including 4 analog)	4 relays 8 A	24 V ===	88970141		
· <u> </u>	6 digital (including 4 analog)	4 solid state 0.5 A (including 1 PWM)	24 V ===	88970142		
XD26	16 digital (including 6 analog)	10 relays (8 x 8 A relay and 2 x 5 A relay)	24 V ===	88970161		
	16 digital (including 6 analog)	10 solid state 0.5 A (including 4 PWM)	24 V ===	88970162		
	16 digital (including 6 analog)	10 relays (8 x 8 A relay and 2 x 5 A relay)	12 V ===	88970165		
	16 digital (including 6 analog)	10 solid state 0.5 A (including 4 PWM)	12 V ===	88970814		
XB10	6 digital (including 4 analog)	4 relays 8 A	24 V ===	Obsolete 88970131		
	6 digital (including 4 analog)	4 solid state 0.5 A (including 1 PWM)	24 V ===	Obsolete 88970132		
XB26	16 digital (including 6 analog)	10 relays (8 x 8 A relay and 2 x 5 A relay)	24 V ===	88970151		
	16 digital (including 6 analog)	10 solid state 0.5 A (including 4 PWM)	24 V ===	88970152		
	16 digital (including 6 analog)	10 relays (8 x 8 A relay and 2 x 5 A relay)	12 V ===	88970155		

Accessories Type M3 Soft Multilingual programming software containing specific library functions (CD-ROM) 88970111 PA 88970108 EEPROM memory cartridge PA 3 m serial programming cable: PC → Millenium 3 88970102 PA USB programing cable 3 m: PC → Millenium 3 88970109 PA 88970104 Millenium 3 interface → Bluetooth® (class A 10 m)

