

Product Image



/publicpictures/Produktbild/9171400401.tif

Master data

Product number:	9171400902
EAN:	4007123675692
Artikelverantwortlicher:	Brennenstuhl Tübingen
manufacturer:	Brennenstuhl
Product line:	professionallINE
Kundenspezifisch:	No
Minimalpflege:	No
Ausleitungskennzeichen:	J
Gewählte Vertriebsregion:	De
Gewählte Sprache:	en

Texts

Is4-Bezeichnung 12:

Profi 360°Akku Strahler ORUM 4050 MH Hybrid, 5700lm, IP65, IK10

Short description for the internet:

Brennenstuhl professionalLINE LED Work Light Hybrid 360° ORUM 4050 MH / LED Construction Light Rechargeable for Permanent Outdoor Use IP65 (40W, 5000lm, 5m cable, BGI 608, ideal for room illumination)

Website-Kurztext:

LED Work Light Hybrid 360° ORUM / LED Construction Light 40W for Permanent Outdoor Use IP65 (5000lm, with 5m Cable and Battery, Perfect All-round Lighting, up to 20h Light Duration)

Print-Kurztext:

professionalLINE Mobile 360° Hybrid LED Spotlight ORUM 4050 MH, 5000lm, IP65

Bulletpoint 1:

LED Construction Light for all-round lighting with 360° beam angle can be operated upright, suspended or mounted on a tripod - ideal for painting work or use on construction sites

Bulletpoint 2:

LED Work Light 360° with up to 20 h lighting duration is perfectly suited for permanent outdoor use thanks to IP65 protection (dustproof and water jet proof)

Bulletpoint 3:

Portable Floodlight for construction sites 40 W for room illumination made of robust, break-proof and impact-resistant plastic housing - with hybrid technology: Battery and mains operation possible

Bulletpoint 4:

Job Site Lighting with glare-free light is operated via the on/off switch and is easy to transport thanks to its all-round carrying handle and practical cable winder

Bulletpoint 5:

Scope of delivery: 1x professionalLINE 360° Hybrid LED Work Light ORUM 4050 MH, with 40 W output, on/off switch and 5 m cable and lithium-ion battery - in best brennenstuhl® quality

Online-Beschreibung:

The professionalLINE Hybrid LED Work Light ORUM by Brennenstuhl is a portable floodlight with 40 W output, which provides perfect all-round lighting thanks to a 360° beam angle. The extremely robust work light can be operated standing, hanging or mounted on a tripod and also convinces with the following features:

- * Robust, break and impact resistant plastic housing
- * With on/off switch
- * Hybrid technology: Battery and mains operation possible
- * Emergency lighting function: switches automatically to battery operation in case of power failure
- * LED spotlight has 3 switching levels: 100 %, 50 % and 25 % - enables even longer lighting duration in battery operation
- * Integrated Li-Ion battery 7.4 V/12.5 Ah with charging indicator
- * Cable: 5 m H05RN-F2x1,0
- * Easy to transport due to all-round carrying handle and cable winder
- * Power: 41,7 W
- * Luminous flux: 5000 lm
- * colour temperature: 6500 K
- * Protection class (IP): IP65

Website description:

The extremely robust LED Work Light Hybrid ORUM with an output of 40 W is perfectly suited for permanent outdoor use thanks to its IP65 protection class and oil-resistant cable. The LED worklight provides wide-area all-round lighting thanks to its 360° beam angle, thus ensuring ideal room illumination with glare-free working light. The portable floodlight can be used upright, suspended or mounted on a tripod and can be operated via the on/off switch. It also convinces with the following features:

- * Robust, break and impact resistant plastic housing
- * Easy to transport due to all-round carrying handle and cable winder
- * Hybrid technology: battery and mains operation possible
- * Emergency lighting function: switches automatically to battery operation in case of power failure
- * LED spotlight has 3 switching levels: 100 %, 50 % and 25 % - enables even longer lighting duration in battery operation
- * Integrated Li-Ion battery 7.4 V/12.5 Ah with charging indicator
- * Cable: 5 m H05RN-F2x1,0
- * Luminous flux: 5000 lm
- * colour temperature: 6500 K
- * Impact strength: IK10
- * BGI 608

Schlagworte:

led spotlight, led spotlight 40w, led spotlight fireplace chair, led spotlight 40w, spotlight flood, spotlight ip54, spotlight, spotlight stand, spotlight fireplace chair, spotlight 41,7W, spotlight outdoor, spotlight outdoor, spotlight outdoor, spotlight 40w, spotlight outdoor, mobile construction spotlight, led spotlight mobile, led floodlight mobile, led spotlight 40w, led spotlight ip54, led spotlight portable, led work light, work light, work light outdoor, work light round, work light outdoor, work light outdoor, work light construction site, led construction spotlight battery, led spotlight battery, led work light battery

Subtitle:

Ideal for indoors and outdoors, IP 65.

Print-Beschreibung:

- * Excellent all-round lighting thanks to 360° beam angle, anti-glare and wide diffusion.
- * Bright light, all the time, even in areas without an electrical connection.
- * Hybrid technology: Battery and mains operation possible.
- * Emergency lighting: automatically switches to battery power during a power outage.
- * LED floodlight has 3 switching levels: 100 %, 50 % and 25 % - allows for an even longer lighting duration in battery operation.
- * Integrated Li-Ion battery 7.4 V/12.5 Ah with charging indicator.
- * The light can be used when placed upright, hanging or mounted on a stand.
- * Robust, break and impact resistant plastic casing.
- * Including power supply unit 100 - 240 V AC, 50/60 Hz and removable 5 m RN cable.
- * With ON/OFF switch.
- * Easy to transport thanks to all-round carry handle and cord wrap.
- * Shock resistance: IK 10.

Infotext:

Table article information:

Scope of supply:

Media



/publicpictures/Logo-Neu/logo-neu-proline-de_en.eps



/publicpictures/icon/icon-norm-bgi-608-k2.eps



/publicpictures/icon/icon-special-robust-baustelle-bauhelm-proline.eps



/publicpictures/icon/icon-schutzart-ip65-proline.eps



/publicpictures/icon/icon-kabellaenge-5m-proline.eps



/publicpictures/icon/icon-stossfest-ik10-proline.eps



/publicpictures/icon/icon-lumen-5000-proline.eps



/publicpictures/icon/icon-ecodesign-erp2021.eps



/publicpictures/Detailansicht/9171400401-anschlussbuchse.tif



/publicpictures/Detailansicht/9171400401-anschlussbuchse-laden.tif



/publicpictures/Detailansicht/9171400401-unten.tif



/publicpictures/Ausstattung/9171400401-stecker.tif




/publicpictures/Ausstattung/9171400401-kabel.tif



/publicpictures/Anwendung/9171400400-baustelle-2-strahler-verbunden.tif



/publicpictures/Anwendung/9171400400-baustelle-stativ-2.tif



/publicpictures/Anwendung/9171400400-baustelle-haengen.tif

/restrictedpictures/QR-Code/9171400902-qr-code-info.eps

/publicvideos/Video-Produkt/professionalLINE/DesktopVersion/011-ORUM_EN.mp4

Context

Attributkategorie:

Light

Accessories:

1170310

Garantie:

3 years

9171991100

1170610020

1172640059



Ersatzteil:

0172640028

Similar products:

/publicpictures/Garantie/icon-garantie-3jahre-en.eps

Technical data

Batterie		Leuchte2Anwendung	
Battery type:	Built-in battery pack	Degree of protection (IP):	IP65
Battery technology:	Lithium-ion	Suitable for outdoor area:	Yes
Rechargeable:	Yes	Impact strength:	IK10
Replaceable:	No	Shock resistance:	Yes
Number of cells:	10	Watertight:	No
Light duration:	20h	Min. operation temperature:	-10°C
Capacity:	12.5Ah	Max. operation temperature:	40°C
Voltage:	7.4V	Leuchte3Stecksystem	
Einsatz im Ex-Bereich - ep:	No	With socket outlet:	No
With battery charging indicator:	Yes	Plug system plug:	other
With battery status indicator:	Yes	Type of plug:	Straight plug
Low-voltage indicator:	No	With usb output:	No
With backup battery:	No	Type of plug - Input:	Hollow plug 2.1 mm
Included backup battery rechargeable:	No	Load input:	Yes
Traction battery:	No	Leuchte4Details	
Power:	92.5Wh	Hammer sign:	Yes
Loading current:	3,500mA	For "complicated conditions" (according to VDE):	Yes
Charging time:	4h	Leuchtmittel0Allgemein	
Dangerous goods regulations:	Yes	Lamp type:	LED non-replaceable
Closed (sealed):	Yes	Nominal frequency:	50/60 Hz
Kabel		Leuchtmittel1Betriebseigenschaften	
Cable designation:	H05RN-F 2X1,0	Life time of light:	35,000h
Cable length:	5m	Energy efficiency class:	F
Cable colour:	black	Lamp efficacy:	119lm/W
Cable entry:	Side	E c (kWh) (= rated energy consumption in 1,000 hours):	42kWh
Cable entry into the housing:	Cable bend relief	Colour temperature:	6,500K
Useful cross section:	1mm ²	Adjustable colour temperature:	No
Leuchte0Allgemein		Fluorescent colour:	white
Type of lamp:	Floodlight	Adjustable luminous flux:	Levels
Housing material:	Plastic		

Housing colour:	black	Luminous flux:	5,000lm
Colour cover:	white	LichtquelleErP	
Colour:	black	Lighting technology used:	LED
Lamp type included:	Yes	Non-directional or directional:	NDLS
Number of lamps:	100	Light source cap-type (or other electric interface):	N/A
Number of batteries:	1	Mains or non-mains:	MLS
Battery included:	Yes	Connected light source (CLS):	No
Rotatable - ep:	Yes	Colour-tuneable light source:	No
Collapsible/ Bendable:	No	High luminance light source:	No
With carrying handle:	Yes	Anti-glare shield:	No
With turn handle:	No	Dimmable:	No
Hook rotatable:	Yes	Energy consumption in on-mode:	42kWh/1000h
Number of hooks:	1	Energy efficiency class:	F
Integrated magnet:	No	Useful luminous flux:	5,000lm
Height adjustable:	No	Beam angle correspondence:	Sphere (360°)
With loudspeaker:	No	Correlated colour temperature type:	Single value
With radio:	No	Correlated colour temperature:	6,500K
With frame:	No	On-mode power:	41.7W
With tripod holder:	No	Standby power:	0.4W
With ground spike:	No	Colour rendering index CRI:	82
With protective grille:	No	Claim of equivalent power:	No
With pocket torch function:	No	Chromaticity coordinate (x):	0.307
Focus:	No	Chromaticity coordinate (y):	0.327
Laserpointer:	No	R9 Colour rendering index:	28
With quick-acting facility:	No	Survival factor:	0.9
With air slots:	No	Lumen maintenance factor:	0.96
Direct/ indirect parts separately adjustable:	No	Displacement factor:	0.9
Energy efficiency class:	F	Colour consistency in McAdam ellipses:	3
E c:	42kWh	Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage:	No
Fluorescent colour:	white		
Adjustable colour temperature:	No	Lifetime (L70B50):	35,000h

Adjustable luminous flux:	Levels	Netzteil	
Luminous flux:	5,000lm	externes Netzteil:	Yes
Suitable for emergency lighting:	Yes	Optionales externes Netzteil verfügbar:	No
Emergency unit integrated:	No	Frequency at external charger unit:	50/60 Hz
With orientation lighting:	No	Output voltage:	12V
Suitable for accent lighting:	No	Min. Nominal input voltage:	220V
Fit for monitor workplace:	No	Max. Nominal input voltage:	240V
Multicolour- switch steps:	No	Output current:	3.5A
Leuchte1elektrWerte		With power supply:	Yes
Protection class:	III	Type of plug - Input:	Type E and F (Protective contact with earth hole)
Power supply:	Hybrid	Type of plug - Output:	Hollow plug 2.1 mm
Load input for external power supply:	Yes	Mgv	
Nominal frequency:	50/60 Hz	Packaging unit (UP):	1
Power consumption:	41.7W	Weight of product (without packaging):	2.85kg
Power consumption in standby mode:	0.4W	Length of product (without packaging):	28cm
Min. Nominal input voltage:	100V	Width of product (without packaging):	28cm
Max. Nominal input voltage:	240V	Height of product (without packaging):	28.5cm
Type of input voltage:	Alternating voltage (AC)	Weight of product (including packaging):	3.51kg
Leuchte2Anwendung		Length of product (including packaging):	28.5cm
With on/off switch:	Yes	Width of product (including packaging):	28.5cm
Illuminated switch:	No	Height of product (including packaging):	30cm
With twilight switch:	No		

articlepreview_icons



/publicpictures/Icon-Energieeffizienz/icon-energieeffizienz-pfeil-f.eps



/publicpictures/Icon-Energieeffizienz/icon-energieeffizienz-pfeil-f.eps

Variantgroup

professionallINE 360° Hybrid LED Construction Worklight ORUM 4050 MH

- * Excellent all-round lighting thanks to 360° beam angle, anti-glare and wide diffusion.
- * Bright light, all the time, even in areas without an electrical connection.
- * Hybrid technology: Battery and mains operation possible.
- * Emergency lighting: automatically switches to battery power during a power outage.
- * LED floodlight has 3 switching levels: 100 %, 50 % and 25 % - allows for an even longer lighting duration in battery operation.
- * Integrated Li-Ion battery 7.4 V/12.5 Ah with charging indicator.
- * The light can be used when placed upright, hanging or mounted on a stand.
- * Robust, break and impact resistant plastic casing.
- * Including power supply unit 100 - 240 V AC, 50/60 Hz and removable 5 m RN cable.
- * With ON/OFF switch.
- * Easy to transport thanks to all-round carry handle and cord wrap.
- * Shock resistance: IK 10.

Related Article

9171400401

9171400902

Variant Differentiation