

datasheet for PRUEF 2600  
 article number: 972317100



<b>product description:</b>	order number: 972 317-100
<b>description:</b>	Test probe with shatter-proof insulating sleeve and slender stainless steel tip. Tip for penetration of insulation and oxide layers. 4 mm diameter brass socket connection. Connects with safety measuring leads.
<b>typ:</b>	PRUEF 2600 schwarz/black
<b>system:</b>	4 mm safety system
<b>order number:</b>	972 317-100
<b>color</b>	●
<b>other color versions:</b>	● ●
<b>technical data</b>	
<b>measurement category</b>	CAT III
<b>norm</b>	DIN EN 61010-031
<b>pin dimensions</b>	2mm
<b>type of contact:</b>	to touch
<b>type of termination:</b>	4 mm socket, unsprung
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b>	1A
<b>contact resistance:</b>	50 mOhm
<b>material</b>	
<b>contact material:</b>	stainless steel
<b>contact surface material:</b>	nickel
<b>housing material:</b>	PP
<b>environmental conditions:</b>	
<b>temperature range:</b>	-25 °C to +80 °C
<b>flammable class:</b>	
<b>housing:</b>	94 HB
<b>drawing</b>	

