



datasheet for PRUEF 2610 FT  
 article number: 972318101



<b>product description:</b>	<b>order number: 972 318-101</b>
<b>description:</b>	Test probe with insulating sleeve and slender, sprung stainless steel tip. This allows a constant pressure to be applied without the tip slipping off the component, even in the smallest measuring points. 4 mm diameter brass socket connection. component part: protector and IC - tap SS 260
<b>typ:</b>	PRUEF 2610 FT rot/red
<b>system:</b>	4mm safety system
<b>order number:</b>	972 318-101
<b>color</b>	
<b>other color versions:</b>	
<b>technical data</b>	
<b>measurement category</b>	CAT II
<b>norm</b>	DIN EN 61010-031
<b>pin dimensions</b>	0,75mm
<b>type of contact:</b>	to touch with spring-mounted spike
<b>type of termination:</b>	4mm socket, unspung
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b>	1A
<b>contact resistance:</b>	50mOhm
<b>material</b>	
<b>contact material:</b>	stainless steel
<b>contact surface material:</b>	rhodium
<b>housing material:</b>	PP
<b>environmental conditions:</b>	
<b>temperature range:</b>	-25 °C to +80 °C
<b>inflammable class:</b>	
<b>housing:</b>	94 HB
<b>drawing</b>	

