

Screwdrivers for slotted screws

IEC 60900 DIN EN 60900

98
2

- > ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- > handle design prevents rolling
- > Chrome vanadium molybdenum steel



98 20 55

98 21 45

especially for meter assembly with blade length of 180 mm

| Article No. | EAN 4003773- | ↔ mm | | Point | Handle | Blade width mm | Blade thickness mm | Blade length mm | Length of non-insulated blade mm | Handle length mm | ⚖ g |
|-------------|--------------|------|--|-----------|---|----------------|--------------------|-----------------|----------------------------------|------------------|-----|
| 98 20 10 | 026396 | 320 | | burnished | insulating multi-component handle, VDE-tested | 10.0 | 1.6 | 200 | 15 | 120 | 184 |
| 98 20 25 | 062325 | 177 | | | | 2.5 | 0.4 | 75 | 15 | 102 | 32 |
| 98 20 30 | 062332 | 202 | | | | 3.0 | 0.5 | 100 | 15 | 102 | 35 |
| 98 20 35 | 024217 | 202 | | | | 3.5 | 0.6 | 100 | 15 | 102 | 35 |
| 98 20 40 | 026402 | 202 | | | | 4.0 | 0.8 | 100 | 15 | 102 | 38 |
| 98 20 55 | 024224 | 232 | | | | 5.5 | 1.0 | 125 | 15 | 107 | 69 |
| 98 20 65 | 026419 | 262 | | | | 6.5 | 1.2 | 150 | 15 | 112 | 105 |
| 98 20 80 | 024231 | 295 | | | | 8.0 | 1.2 | 175 | 15 | 120 | 152 |
| 98 21 45 | 026426 | 287 | | burnished | insulating multi-component handle, VDE-tested | 4.5 | 0.8 | 180 | 15 | 107 | 66 |

Screwdrivers (Slim) for slotted screws

IEC 60900 DIN EN 60900

98
2

- > Reduced blade isolation diameter for recessed spring and screw elements
- > ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- > handle design prevents rolling
- > Chrome vanadium molybdenum steel



98 20 65 SL

| Article No. | EAN 4003773- | ↔ mm | | Point | Handle | Blade width mm | Blade thickness mm | Blade length mm | Length of non-insulated blade mm | Handle length mm | ⚖ g |
|-------------|--------------|------|--|-----------|---|----------------|--------------------|-----------------|----------------------------------|------------------|-----|
| 98 20 35 SL | 079712 | 202 | | burnished | insulating multi-component handle, VDE-tested | 3.5 | 0.6 | 100 | 15 | 102 | 35 |
| 98 20 40 SL | 079729 | 202 | | | | 4.0 | 0.8 | 100 | 15 | 102 | 38 |
| 98 20 55 SL | 079736 | 232 | | | | 5.5 | 1.0 | 125 | 15 | 107 | 69 |
| 98 20 65 SL | 079743 | 262 | | | | 6.5 | 1.2 | 150 | 15 | 112 | 105 |

Screwdrivers for cross-recessed screws

Phillips®
IEC 60900 DIN EN 60900

98
2

- > ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- > handle design prevents rolling
- > Chrome vanadium molybdenum steel



98 24 03

Phillips® is a registered trademark of Phillips Screw Company

| Article No. | EAN 4003773- | ↔ mm | | Point | Handle | Size | Blade length mm | Length of non-insulated blade mm | Handle length mm | ⚖ g |
|-------------|--------------|------|--|-----------|---|------|-----------------|----------------------------------|------------------|-----|
| 98 24 00 | 026433 | 162 | | burnished | insulating multi-component handle, VDE-tested | PH0 | 60 | 15 | 102 | 32 |
| 98 24 01 | 026440 | 187 | | | | PH1 | 80 | 15 | 107 | 58 |
| 98 24 02 | 026457 | 212 | | | | PH2 | 100 | 18 | 112 | 94 |
| 98 24 03 | 026464 | 270 | | | | PH3 | 150 | 18 | 120 | 165 |
| 98 24 04 | 026471 | 320 | | | | PH4 | 200 | 18 | 120 | 244 |