

## RACK PDU, BASIC, 0U/1U, 120-240V/15A, 220-240V/10A, (8) C13

### AP6015A

Call for More Information 0800 2799254



- Includes: Installation guide, Safety guide

Output	
Nominal Output Voltage	100V, 120V, 200V, 208V, 230V, 240V
Maximum Total Current Draw	15
Output Connections	(8) IEC 60320 C13

Input	
Nominal Input Voltage	100V, 120V, 200V, 208V, 230V, 240V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C14
Acceptable Input Voltage	100 - 240VAC
Load Capacity	2300VA
Maximum Input Current	15A
Maximum Line Current	15A
Regulatory Derated Input Current (North America)	12A

Physical	
Maximum Height	240MM, 24.0CM
Maximum Width	44MM, 4.4CM
Maximum Depth	93MM, 9.3CM
Rack Height	1U
Net Weight	0.91KG
Shipping weight	1.37KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Physical	
Shipping Height	286MM, 28.6CM
Shipping Width	210MM, 21.0CM
Shipping Depth	130MM, 13.0CM
Color	Black
Units per Pallet	192.0

  

Conformance	
Approvals	CE, cUL listed, EAC, IRAM, UL listed, VDE
Standard warranty	2 years repair or replace

  

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.