

Rack PDU, Basic, 0U/1U, 100-240V/20A, 220-240V/16A, (13) C13

AP6020A

Call for More Information 0800 2799254



- Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (13) C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
- Includes: Installation guide, Safety guide

Output	
Maximum Total Current Draw	20
Output Connections	(13) IEC 60320 C13

Input	
Nominal Input Voltage	100V, 120V, 200V, 208V, 230V, 240V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Acceptable Input Voltage	100 - 240VAC
Load Capacity	3300VA
Maximum Input Current	20A
Maximum Line Current	20A
Regulatory Derated Input Current (North America)	16A

Physical	
Maximum Height	388MM, 38.8CM
Maximum Width	44MM, 4.4CM
Maximum Depth	93MM, 9.3CM
Rack Height	1U
Net Weight	1.5KG
Shipping weight	2.02KG
Shipping Height	436MM, 43.6CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Width	210MM, 21.0CM
Shipping Depth	76MM, 7.6CM
Color	Black
Units per Pallet	100.0

Conformance	
Approvals	CE, cUL listed, EAC, IRAM, PSE, UL listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.